

MEDIUM PRESSURE AIR COOLED MARINE AIR COMPRESSOR

Medium Pressure 3.0MPa Two Stage
Compression Tanabe Air Compressor
LSHC Series

ISO9001 Supplier

Class Certificate

Export Supply

Condition:New Type:Piston Configuration:Portable Power Source:AC Power Lubrication
Style:Lubricated Mute:No Place of Origin:Chongqing, China (Mainland) Certification:CCS
Warranty:1 Year Cooling type: air co...



Key Highlights

Category	Medium Pressure Air Cooled Marine Air Compressor
Standard	GB
Weight / Size	air cooled After-sales Service Provided:Overseas service center availab...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement,
drawings, class certificate needs, and delivery
schedule.

Technical Specifications			
Category	Medium Pressure Air Cooled Marine Air Compressor	Model / SKU	Medium-Pressure-3-0MPa-Two-Stage-Compression-Marine-Air-Compressor-LSHC-Series
Standard	GB	Weight / Size	air cooled After-sales Service Provided:Overseas service center available Parameter Compressor Model LSHC-20B LSHC-30A LSHC-40A MSHC-40A Type Vertical Air-Cooled 2 stage Compression Quantity of Air Supply (m3/h) 5 13.5 20 20 Pressure Rating (MPa) 3 Stalk Power (kw) 1.6 4 5.5 5.5 Rotation Rating (r/min) 940 960 Lubricating System Splash Lubrication Lubricate Trademark L-DAB-100 (GB12691) Type of Unloader Manual,Total closure suction type or Magnetic Unloader Valve Method of Driving Direct Coupling Motor model Y112M-6-H Y132S-4-H Y132M-6-H Y160M2-8-H Power (kw) 2.2 5.5 5.5 5.5 Rotation (r/min) 940 1440 960 870 Gradeprotection IP44 Ins Class B Voltage(V) 380 380 380 440 Frequency(HZ) 50 50 50 60 Shape size(mm) 670×450×470 1140×520×810 1020×580×900 1020×580×900 Weight(kg) 130 280
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	China Medium Pressure 3.0MPa Two Stage Compression Tanabe Air Compressor LSHC Series:	Parameter
----------	---	---

China Medium Pressure 3.0MPa Two Stage Compression Tanabe Air Compressor LSHC Series:

Condition:New

Type:Piston

Configuration:Portable

Power Source:AC Power

Lubrication Style:Lubricated
Mute:No
Place of Origin:Chongqing, China (Mainland)
Certification:CCS
Warranty:1 Year
Cooling type: air cooled
After-sales Service Provided:Overseas service center available

Parameter

Compressor Model	LSHC-20B	LSHC-30A	LSHC-40A	MSHC-40A
Type	Vertical Air-Cooled 2 stage Compression			
Quantity of Air Supply （m3/h）	5	13.5	20	20
Pressure Rating （MPa）	3			
Stalk Power （kw）	1.6	4	5.5	5.5
Rotation Rating （r/min）	940	960		
Lubricating System	Splash Lubrication			
Lubricate Trademark	L-DAB-100（ GB12691）			
Type of Unloader	Manual,Total closure suction type or Magnetic Unloader Valve			
Method of Driving	Direct Coupling			
Motor				
model	Y112M-6-H	Y132S-4-H	Y132M-6-H	Y160M2-8-H
Power （kw）	2.2	5.5	5.5	5.5
Rotation（r/min）	940	1440	960	870
Gradeprotection	IP44			
Ins Class	B			
Voltage(V)	380	380	380	440
Frequency(HZ)	50	50	50	60
Shape size(mm)	670×450×470	1140×520×810	1020×580×900	1020×580×900
Weight(kg)	130	280		