

LIFE-SAVING LIGHT

ML-OS155-03 Marine Signal Lantern

ML-OS155-03 lantern is a newly developed Self Contained Solar Power LED Marine Signal Lantern that has 3 intensity outputs ranging 1, 2 and 3 nautical miles for site selection.ML-OS155-03 lantern has characters of easy i...

ISO9001 Supplier

Class Certificate

Export Supply

Loading product image...

Key Highlights

Category	Life-Saving Light
Standard	EN
Weight / Size	Super bright LED save energy Patent optic design insure highlight effici...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Life-Saving Light	Model / SKU	ML-OS155-03-Marine-Signal-Lantern
Standard	EN	Weight / Size	Super bright LED save energy Patent optic design insure highlight efficiency High horizontal intensity uniformity Computer chip control achieve high reliability Remote programmer select range and rhythm / No need to open lantern UV resistant PC for lens Plastic base with anti - UV treatment suitable for marine environment Light weight and easy installation Specifications:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China ML-OS155-03 Marine Signal Lantern:
- Specifications:
- Features:

China ML-OS155-03 Marine Signal Lantern:

ML-OS155-03 lantern is a newly developed Self Contained Solar Power LED Marine Signal Lantern that has 3 intensity outputs ranging 1, 2 and 3 nautical miles for site selection. ML-OS155-03 lantern has characters of easy installation, no need of battery box and maintenance free. It is widely used on light buoys and beacons at sea.

Features:

Super bright LED save energy

Patent optic design insure highlight efficiency

High horizontal intensity uniformity

Computer chip control achieve high reliability

Remote programmer select range and rhythm / No need to open lantern

UV resistant PC for lens

Plastic base with anti - UV treatment suitable for marine environment

Light weight and easy installation

Specifications:

Light source: Super bright LED

Vertical divergence: 7.5(150%)

Sun switch: 250t50 lx

Flash rhythm: 256 rhythms site selectable

Idling current: 54mA Solar panel: 2W

Maintenance-free battery: 8Ah

Autonomy (50% flash, 12hr/day): 3nm:212 day; 2nm:224 day; 1nm:272 day.

Temperature: -35C~+55C

Protection: IP68

Dimension: 240x285mm Installation: 3 and 4-17 on 200mm bolt circle

Weight: 1.6kg

Optional: GPS synchronized flash

Available range: 1NM, 2NM, 3NM