

MANUAL OPERATED FIRE MONITOR

Moveable Fire Monitor PSY30-80

Type: PSY80A Weight : Approx 20KG Flow Range: 10-80 L/S Automatic Nozzle Working Pressure: 10 bar Max Reach @ Max Flow: 80m Range of motion: 0°~+90°Vert , 360°Rot Max fog angle : 120° Monitor Outlet : 2.5 inch (65mm) ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	0°~+90°Vert , 360°Rot Max fog angle : 120° Monitor Outlet : 2.5 inch (65mm)...
Weight / Size	PSY80A Weight : Approx 20KG Flow Range:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	Model / SKU	Moveable-Fire-Monitor-PSY30-80
Standard	EN	Material	0°~+90°Vert , 360°Rot Max fog angle : 120° Monitor Outlet : 2.5 inch (65mm) Monitor Inlet : 2.5 inch X 2 couplings Material (body) : Aluminum Material (Gear) : Aluminum Material (nozzle) : Aluminum Horizontal Control : Lever Action Rotational Lock Vertical Control : Handwheel (6 Inch, Injection Molded Nylon) Pump requirement for minimum performance : 10L/S@ 8 bar Inlet coupling is hose anti-knot ,360 degree rotatable Foam attachment is available for foam fire fighting Paint:
Weight / Size	PSY80A Weight : Approx 20KG Flow Range:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Moveable Fire Monitor PSY30-80:

Type: PSY80A

Weight : Approx 20KG

Flow Range: 10-80 L/S Automatic Nozzle

Working Pressure: 10 bar

Max Reach @ Max Flow: 80m

Range of motion: 0°~+90°Vert , 360°Rot

Max fog angle : 120°

Monitor Outlet : 2.5 inch (65mm)

Monitor Inlet : 2.5 inch X 2 couplings

Material (body) : Aluminum

Material (Gear) : Aluminum

Material (nozzle) : Aluminum

Horizontal Control : Lever Action Rotational Lock

Vertical Control : Handwheel (6 Inch, Injection Molded Nylon)

Pump requirement for minimum performance : 10L/S@ 8 bar

Inlet coupling is hose anti-knot ,360 degree rotatable

Foam attachment is available for foam fire fighting

Paint: Fire Red

