RUBBER SHEET

Natural Rubber Sheet

ISO9001 Supplier

Class Certificate

Export Supply

Size: Thickness 1 to 50mm. Wide: 500 to 3000mm. Density:1.05 to 1.3 g/cm3.   Tensile Strength: 12 to 20Mpa. Elongation: 450 to 650%. Hardness: 35 to 50 shore-A Application: Widely used in electroni...



Key Highlights

Category	Rubber Sheet
Standard	EN
Material	As oil resistant material.
Weight / Size	Size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Rubber Sheet	**Model / SKU**	Natural-Rubber-Sheet
Standard	EN	**Material**	As oil resistant material.
Weight / Size	Size:	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China Natural Rubber Sheet:
- Feature:
- Application:

China Natural Rubber Sheet:

Size:

Thickness 1 to 50mm. Wide: 500 to 3000mm.

Density:1.05 to 1.3 g/cm3.

Tensile Strength: 12 to 20Mpa.

Elongation: 450 to 650%.

Hardness: 35 to 50 shore-A

Application:

Widely used in electronics.

Thermal aging site.

As oil resistant material.

Feature:

Good resistance to heat. Good resistance to ozone. Good elasticity.