

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE NAVIGATION SIGNAL LIGHT

# Navigation Signal Light CXH-3P

The Navigation Signal Light used to the ship with length 12M or above as lamp signal liaison when night navigation.

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

<b>Category</b>	Marine Navigation Signal Light
<b>Standard</b>	ISO
<b>Material</b>	Engineering Plastic, Steel, Stainless Steel
<b>Weight / Size</b>	Type CXH1-3P,CXH2-3P,CXH3-3P,CXH4-3P CXH6-3P Voltage 12V 24V 12V 24V Pow...
<b>Certificate</b>	CCS Type Approval Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Marine Navigation Signal Light	<b>Model / SKU</b>	Navigation-Signal-Light-CXH-3P
<b>Standard</b>	ISO	<b>Material</b>	Engineering Plastic, Steel, Stainless Steel
<b>Weight / Size</b>	Type CXH1-3P,CXH2-3P,CXH3-3P,CXH4-3P CXH6-3P Voltage 12V 24V 12V 24V Power 25W 25W 25W Luminous Intensity 40cd 60cd 40cd 60cd Lamp Holder Bay15d Protection Class IP56 Cable Diameter Dia.9 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-3P 1n.m 112.5o Green 0.53KGS Port Light CXH2-3P 1n.m 112.5o Red 0.53KGS Masthead Light CXH3-3P 2n.m 225o White 0.53KGS Stern Light CXH4-3P 2n.m 135o White/Yellow 0.53KGS All-round-Light CXH6-3P 2n.m 360o Red/green/white 0.53KGS	<b>Certificate</b>	CCS Type Approval Certificate
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ China Navigation Signal Light CXH-3P:</li> <li>■ Standards:</li> </ul>	<ul style="list-style-type: none"> <li>■ Product Advantage:</li> <li>■ Main Specification:</li> </ul>
-----------------	---	---

## China Navigation Signal Light CXH-3P:



The Navigation Signal Light used to the ship with length 12M or above as lamp signal liaison when night navigation.

## Product Advantage:

1. The signal lights have the seal structure, waterproof under the extreme environment.
2. The shell is made of high-strength engineering plastic PA+GF, the lamp shade use injection of PC, lens hood of good quality
3. Special light bulb with average life up to 700hrs.
4. Working Temperature:-30°C-55°C

## Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

## Main Specification:

Type	CXH1-3P,CXH2-3P,CXH3-3P,CXH4-3P		CXH6-3P	
Voltage	12V	24V	12V	24V
Power	25W	25W	25W	25W
Luminous Intensity	40cd	60cd	40cd	60cd
Lamp Holder	Bay15d			
Protection Class	IP56			
Cable Diameter	Dia.9			

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-3P	1n.m	112.5°	Green	0.53KGS
Port Light	CXH2-3P	1n.m	112.5°	Red	0.53KGS
Masthead Light	CXH3-3P	2n.m	225°	White	0.53KGS
Stern Light	CXH4-3P	2n.m	135°	White/Yellow	0.53KGS
All-round- Light	CXH6-3P	2n.m	360°	Red/green/white	0.53KGS