

MARINE TOOLS

Non-sparking 1/4 inch Sockets

Non-sparking 1/4 inch Sockets: Uses: In flammable and explosive places, used in places with special positions and narrow spaces, used in spaces where adjustable wrenches and open wrenches cannot be used, used for f...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Tools
Standard	EN
Material	Beryllium bronze alloy, Aluminum Copper alloy
Weight / Size	Material : Beryllium bronze alloy, Aluminum Copper alloy Socket 1/4 inch W...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Tools	Model / SKU	Non-sparking-1-4-inch-Sockets
Standard	EN	Material	Beryllium bronze alloy, Aluminum Copper alloy
Weight / Size	Material : Beryllium bronze alloy, Aluminum Copper alloy Socket 1/4 inch Weight (g) S mm L mm Aluminum Bronze Beryllium Copper 4 25 15 17 4.5 25 15 17 5 25 15 17 5.5 25 15 17 6 25 15 17 7 25 15 17 8 25 15 17 10 25 20 21 11 25 20 22 12 26 25 27 13 26 27 30 14 26 32 35 15 27 36 40 16 27 36 40 17 27 45 50 18 27 45 50 19 27 46 51 Socket 1/4 inch Weight (g) S inch L mm Aluminum Bronze Beryllium Copper 5/32 25 13 14 3/16 25 13 14 7/32 25 15 17 1/4 25 15 17 9/32 25 15 17 5/16 25 18 20 11/32 26 22 24 3/8 26 26 29 7/16 26 26 29 1/2 26 26 29	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

Non-sparking 1/4 inch Scokets:

Uses: In flammable and explosive places, used in places with special positions and narrow spaces, used in spaces where adjustable wrenches and open wrenches cannot be used, used for fastening or removing hexagon bolts and nuts.

Material : Beryllium bronze alloy, Aluminum Copper alloy

Socket 1/4 inch		Weight (g)	
S mm	L mm	Aluminum Bronze	Beryllium Copper
4	25	15	17
4.5	25	15	17
5	25	15	17
5.5	25	15	17
6	25	15	17
7	25	15	17
8	25	15	17

10	25	20	21
11	25	20	22
12	26	25	27
13	26	27	30
14	26	32	35
15	27	36	40
16	27	36	40
17	27	45	50
18	27	45	50
19	27	46	51

Socket 1/4 inch		Weight (g)	
S inch	L mm	Aluminum Bronze	Beryllium Copper
5/32	25	13	14
3/16	25	13	14
7/32	25	15	17
1/4	25	15	17
9/32	25	15	17
5/16	25	18	20
11/32	26	22	24
3/8	26	26	29
7/16	26	26	29
1/2	26	26	29