

MARINE TOOLS

Non-Sparking Torx Screwdriver

These Non-Sparking Torx Screwdriver are made of Aluminum Bronze and Beryllium Copper, it is a high quality grade beryllium copper alloy material and a standard grade aluminum-bronze alloy. These tools ar...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Tools
Standard	These Non-Sparking Torx Screwdriver are made of Aluminum Bronze and Bery...
Material	Aluminum Bronze, Beryllium Copper
Weight / Size	Size L1 inch L mm Weight (g) Aluminum Bronze Beryllium Copper T10*75 75 ...
Certificate	EACC, IAF

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Tools	Model / SKU	Non-Sparking-Torx-Screwdriver
Standard	These Non-Sparking Torx Screwdriver are made of Aluminum Bronze and Beryllium Copper, it is a high quality grade beryllium copper alloy material and a standard grade aluminum-bronze alloy.	Material	Aluminum Bronze, Beryllium Copper
Weight / Size	Size L1 inch L mm Weight (g) Aluminum Bronze Beryllium Copper T10*75 75 180 63 70 T15*75 75 180 63 70 T20*100 100 215 95 100 T25*125 125 240 100 105 T30*150 150 265 100 110 T40*200 200 327 155 165 T45*250 300 377 175 185 T50*300 350 427 195 205 T55*350 350 500 225 245 T60*400 400 550 255 280	Certificate	EACC, IAF
Warranty	12 Months unless specified otherwise	Origin	China

China Non-Sparking Torx Screwdriver:

These Non-Sparking Torx Screwdriver are made of Aluminum Bronze and Beryllium Copper, it is a high quality grade beryllium copper alloy material and a standard grade aluminum-bronze alloy. These tools are non-magnetic and non-corrosion, very suitable used for LPG and LNG vessels, and oil-gas industry etc.

Size	L1 inch	L mm	Weight (g)	
			Aluminum Bronze	Beryllium Copper
T10*75	75	180	63	70
T15*75	75	180	63	70
T20*100	100	215	95	100
T25*125	125	240	100	105
T30*150	150	265	100	110
T40*200	200	327	155	165
T45*250	300	377	175	185
T50*300	350	427	195	205
T55*350	350	500	225	245

T60*400	400	550	255	280
---------	-----	-----	-----	-----