

DIVING AIR COMPRESSOR

NRX6 Portable High Pressure Diving Air Compressor

Medium: Air Ambient temperature: - 20~+50°C Safety valve setting: 330 bar Working Pressure: 330 bar Number of Compression stages: 4 Number of Cylinders: 4 Drive: V-Belt Breathing ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Diving Air Compressor
Standard	ISO
Weight / Size	0.3 L Intake filter element Setting cooler after every compressed After ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Diving Air Compressor	Model / SKU	NRX6-Portable-High-Pressure-Diving-Air-Compressor
Standard	ISO	Weight / Size	0.3 L Intake filter element Setting cooler after every compressed After compresses gas through the cooler, and its temp is higher around 10-15°C then the ambient temperature Intermediate oil/water separators after each stage (except 1st stage) Final Oil/water separator Final pressure safety valve Compressor equipped with pressure maintenance valve NRX6 Portable High Pressure Diving Air Compressor Main Specifications Model Nominal Pressure Free Air Delivery Power Outlet Dimensions Weight Mpa L/min KW mm mm Kg NRX6 15~30 100 2.2 ZG1/4 650*400*410 45 NRX6B 15~30 100 2.2 ZG1/4 505*505*760 85
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China NRX6 Portable High Pressure Diving Air Compressor: ■ NRX6 Portable High Pressure Diving Air Compressor Main Specifications	■ Compressor Main Units
----------	---	---

China NRX6 Portable High Pressure Diving Air Compressor:

- Medium: Air
- Ambient temperature: - 20~+50°C
- Safety valve setting: 330 bar
- Working Pressure: 330 bar
- Number of Compression stages: 4
- Number of Cylinders: 4
- Drive: V-Belt
- Breathing air standard: EN12021
- Product Certification: Exported EU CE certification, CCS SOLAS, ISO 9001 quality system

Compressor Main Units

Splash lubrication

Oil sump content: 0.3 L

Intake filter element

Setting cooler after every compressed

After compresses gas through the cooler, and its temp is higher around 10-15°C then the ambient temperature

Intermediate oil/water separators after each stage (except 1st stage)

Final Oil/water separator

Final pressure safety valve

Compressor equipped with pressure maintenance valve

NRX6 Portable High Pressure Diving Air Compressor Main Specifications

Model	Nominal Pressure	Free Air Delivery	Power	Outlet	Dimensions	Weight
	Mpa	L/min	KW	mm	mm	Kg
NRX6	15~30	100	2.2	ZG1/4	650*400*410	45
NRX6B	15~30	100	2.2	ZG1/4	505*505*760	85