

MARINE COMMUNICATION EQUIPMENT

NTW-1000 Two-Way VHF

FEATURES: Compact, lightweight and rugged construction. Easy operation, even for unskilled personnel. Full marine-use VHF channels. Designed to meet GMDSS requirements related with performance standards for survival...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Communication Equipment
Standard	EN
Weight / Size	Compact, lightweight and rugged construction.
Certificate	CCS,MED,VR type approval certificate.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Communication Equipment	Model / SKU	NTW-1000-Two-Way-VHF
Standard	EN	Weight / Size	Compact, lightweight and rugged construction.
Certificate	CCS,MED,VR type approval certificate.	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ FEATURES:

■ Speification:

FEATURES:

Compact, lightweight and rugged construction.
Easy operation, even for unskilled personnel.
Full marine-use VHF channels.
Designed to meet GMDSS requirements related with performance standards for survival craft two-way VHF Radiotelephone apparatus, such as IMO M.149(77) and IEC 61097-12.

Speification:

Technical Specifications	
Frequency Range:	156.025 ~ 162.975MHz
Operating Channels:	19 channels (default)
Operating Hours:	≥8 hours (TX10%, RX10%, Standby80%)
Output Power:	High 3.0W / Low 0.5w
Battery Requirements	
Battery Voltage:	DC 7.2V
Storage Temp.:	-30°C~+70°C
Storage Time:	5 years on board (see Note 1)
Dimension & Weight	
Dimension:	256(H) X 51.4(W) X 46.2(D) mm
Weight:	400g (Transceiver+Emergency Battery)
IP Grade:	IP67 (Transceiver / Battery) IP22 (Charger / Adaptor)