


FLAME ARRESTOR

Oil Tank Flame Arrestor

We can supply all kinds of Oil Tank Flame Arrestor, High quality, Fast Delivery; Customized Service available

- ISO9001 Supplier
- Class Certificate
- Export Supply

	<div style="background-color: #1a3d3d; color: white; padding: 5px;">Key Highlights</div> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Category</td> <td>Flame Arrestor</td> </tr> <tr> <td>Material</td> <td>L2 A3 304 304L 316 316L</td> </tr> <tr> <td>Certificate</td> <td>ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS</td> </tr> </table> <p style="font-size: small; margin-top: 10px;">We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>	Category	Flame Arrestor	Material	L2 A3 304 304L 316 316L	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Category	Flame Arrestor						
Material	L2 A3 304 304L 316 316L						
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS						

Technical Specifications			
Category	Flame Arrestor	Model / SKU	Oil-Tank-Flame-Arrestor
Material	L2 A3 304 304L 316 316L	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	<ul style="list-style-type: none"> ■ Flame Arrestor 	<ul style="list-style-type: none"> ■ Main Specification
-----------------	--	--



Flame Arrestor

- 1.Installation type Middle of Pipe.
- 2.Working temperature <480.
- 3.Explosive-proof grade BS5501 .

Main Specification

DN	D1	D2	D3	H	N×Φ
50	110	140	192	178	3×14
80	150	185	248	218	4×18
100	170	205	278	238	4×18
150	225	260	354	282	4×18
200	280	315	426	290	4×18