

MARINE FENDER

Pile Guide Roller

Product Description It is commonly used on the berth corners and dock entrances, also widely installed along the walls of dry docks and other restricted channels to help guide vessels and prevent hull damage. ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fender
Standard	DIN
Material	Steel,natural rubber
Weight / Size	Standard Size of Rolling Rubber Fender Type D1 Specification and size V...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Fender	Model / SKU	Pile-Guide-Roller
Standard	DIN	Material	Steel,natural rubber
Weight / Size	Standard Size of Rolling Rubber Fender Type D1 Specification and size \Item A B C D E F D1-060-20 600 200 320 110 420 695 D1-075-25 750 250 400 140 510 870 D1-090-30 900 300 480 165 610 1040 D1-120-40 1200 400 640 220 820 1380 D1-150-50 1500 500 800 275 1010 1740 D1-180-60 1800 600 960 330 1210 2080 D1-210-70 2100 700 1155 385 1410 2440 D1-240-80 2400 800 1280 440 1610 2770 Standard Size of Rolling Rubber Fender Type D2 Specification and size \Item A B C D E F D2-060-20 600 200 320 110 770 695 D2-075-25 750 250 400 140 935 870 D2-090-30 900 300 480 165 1120 1040 D2-120-40 1200 400 640 220 1500 1380 D2-150-50 1500 500 800 275 1850 1740 D2-180-60 1800 600 960 330 2215 2080 D2-210-70 2100 700 1155 385 2590 2440 D2-240-80 2400 800 1280 440 2950 2770 We can customized the size according to your requirement.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Pile Guide Roller:

Product Description

It is commonly used on the berth corners and dock entrances, also widely installed along the walls of dry docks and other restricted channels to help guide vessels and prevent hull damage.

Feature

- 1.Widely used in ports and docks.
- 2.Agile-turning, easy-installation.

Standard Size of Rolling Rubber Fender Type D1

Specification and size \Item	A	B	C	D	E	F
------------------------------	---	---	---	---	---	---

D1-060-20	600	200	320	110	420	695
D1-075-25	750	250	400	140	510	870
D1-090-30	900	300	480	165	610	1040
D1-120-40	1200	400	640	220	820	1380
D1-150-50	1500	500	800	275	1010	1740
D1-180-60	1800	600	960	330	1210	2080
D1-210-70	2100	700	1155	385	1410	2440
D1-240-80	2400	800	1280	440	1610	2770

Standard Size of Rolling Rubber Fender Type D2

Specification and size \Item	A	B	C	D	E	F
D2-060-20	600	200	320	110	770	695
D2-075-25	750	250	400	140	935	870
D2-090-30	900	300	480	165	1120	1040
D2-120-40	1200	400	640	220	1500	1380
D2-150-50	1500	500	800	275	1850	1740
D2-180-60	1800	600	960	330	2215	2080
D2-210-70	2100	700	1155	385	2590	2440
D2-240-80	2400	800	1280	440	2950	2770

We can customized the size according to your requirement.