

DIESEL ENGINE DRIVEN WATER PUMP

Portable diesel fire pump

Portable diesel fire pump Parameter Portable diesel fire pump Set Model 10A 18A ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Diesel engine driven water pump
Standard	EN
Weight / Size	Head lift(m) 45 60 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capa...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Diesel engine driven water pump	Model / SKU	Portable-diesel-fire-pump
Standard	EN	Weight / Size	Head lift(m) 45 60 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capacity(m3/h) 45 84 Max.Head lift(m) 50 65 Engine Engine model 188FB R2V870 Cylinder number single double Engine type 4-stroke,air cooled, gasoline engine BorexStroke(mm) 88x75 88x72 Displacement(ml) 456 870 Rated power(kw) 5.7 13 Max.output power(HP) 13 24 Rated spee(RPM) 3000 3000 Mix.Spee(RPM) <1300 <1300 Fuel consumption ratio(g/kw.h) <285 <289 Fuel type 0#(summer), -10# (winter) Oil type SAE15W-40 starting method Electric start Fuel tank capacity(L) 5.5 5.5 Oil capacity(L) 1.65 1.65 Pack Packing size(mm) 810x750x640 810x750x650 Net weight(Kgs) 65 105 Gross weight(Kgs) 80 115
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ Portable diesel fire pump	■ Parameter
----------	-----------------------------	-------------

Portable diesel fire pump

Parameter

Portable diesel fire pump

Set	Model	10A	18A
	Name	Portable diesel fire pump	
	Inlet/Outlet diameter	65mm(2.5")	80mm(3")
	Cont. Capacity(m3/h)	30	60
	Cont. Head lift(m)	45	60
	Suction.Time	20s	20s
	Max.Suction head(m)	8	8
	Max.Capacity(m3/h)	45	84
	Max.Head lift(m)	50	65
Engine	Engine model	188FB	R2V870
	Cylinder number	single	double
	Engine type	4-stroke,air cooled, gasoline engine	
	BorexStroke(mm)	88x75	88x72
	Displacement(ml)	456	870
	Rated power(kw)	5.7	13
	Max.output power(HP)	13	24
	Rated spee(RPM)	3000	3000
	Mix.Spee(RPM)	<1300	<1300
	Fuel consumption ratio(g/kw.h)	<285	<289
	Fuel type	0#(summer), -10#(winter)	
	Oil type	SAE15W-40	
	starting method	Electric start	
	Fuel tank capacity(L)	5.5	5.5
	Oil capacity(L)	1.65	1.65
Pack	Packing size(mm)	810x750x640	810x750x650
	Net weight(Kgs)	65	105
	Gross weight(Kgs)	80	115