

OTHER FIRE-FIGHTING EQUIPMENT

Portable Explosion Proof Hand Lamps

Shell material chooses ZDL-102 aluminum alloy die-casting molding,and coated wiht good protective lacquer layer.Lamps shell seal no hole,the dry reed pipe and stong magnetic switch structure,ensure explosion proof per...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Other Fire-Fighting Equipment
Standard	DIN
Material	Shell material chooses ZDL-102 aluminum alloy die-casting molding,and co...
Weight / Size	Rated Voltage:7.2V/0.5A Charging time:more than 3h Explosion-proof class...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Other Fire-Fighting Equipment	Model / SKU	Portable-Explosion-Proof-Hand-Lamps
Standard	DIN	Material	Shell material chooses ZDL-102 aluminum alloy die-casting molding,and coated wiht good protective lacquer layer.Lamps shell seal no hole,the dry reed pipe and stong magnetic switch structure,ensure explosion proof performance.
Weight / Size	Rated Voltage:7.2V/0.5A Charging time:more than 3h Explosion-proof class:IP65 Flux:130 Temperatureresistance:200C--+500C Max range:300M Battery:Dry battery Size:130*225MM Weight:1.1KGS	Certificate	CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ China Portable Explosion Proof Hand Lamps:

■ Specification:

China Portable Explosion Proof Hand Lamps:

Shell material chooses ZDL-102 aluminum alloy die-casting molding,and coated wiht good protective lacquer layer.Lamps shell seal no hole,the dry reed pipe and stong magnetic switch structure,ensure explosion proof performance.

Lamps have safe screw,to ensure that in flammable and explosive place open lamps and lanterns.

The lamps is widely used in ship customs,ports,airports,public security fire control,frontier armed police and dangerous goods truck and other places.

DF-6 Portable Explosion-Proof Lamp with Dry Cell

Specification:

Rated Voltage:7.2V/0.5A

Charging time:more than 3h

Explosion-proof class:IP65

Flux:130

Temperatureresistance:200C--+500C

Max range:300M

Battery:Dry battery

Size:130*225MM

Weight:1.1KGS