

GASOLINE ENGINE DRIVEN WATER PUMP

Portable gasoline fire pump

Portable gasoline fire pump Parameter Portable gasoline fire pump Set Model 13A-G 20A-G

...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Gasoline engine driven water pump
Standard	EN
Weight / Size	Head lift(m) 65 65 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capa...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Gasoline engine driven water pump	Model / SKU	Portable-gasoline-fire-pump
Standard	EN	Weight / Size	Head lift(m) 65 65 Suction.Time 20s 20s Max.Suction head(m) 8 8 Max.Capacity(m3/h) 45 51 Max.Head lift(m) 75 75 Engine Engine model G390 G620 Cylinder number single double Engine type 4-stroke,air cooled, gasoline engine BorexStroke(mm) 88x75 77x66 Displacement(ml) 397 598 Rated power(kw) 5.7 15 Max.output power(HP) 13 20 Rated spee(RPM) 3000 3000 Mix.Spee(RPM) <1300 <1300 Fuel consumption ratio(g/kw.h) <390 <395 Fuel type 90#,93#,97# Oil type SAE15W-40 starting method Electric start Fuel tank capacity(L) 6 10 Oil capacity(L) 1.1 1.3 Pack Packing size(mm) 810x490x550 850x910x690 Net weight(Kgs) 65 67 Gross weight(Kgs) 80 90
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ Portable gasoline fire pump	■ Parameter
----------	-------------------------------	-------------

Portable gasoline fire pump

Parameter

Portable gasoline fire pump

Set	Model	13A-G	20A-G
	Name	Portable gasoline fire pump	
	Inlet/Outlet diameter	65mm(2.5")	80mm(3")
	Cont. Capacity(m3/h)	37.2	37.2
	Cont. Head lift(m)	65	65
	Suction.Time	20s	20s
	Max.Suction head(m)	8	8
	Max.Capacity(m3/h)	45	51
	Max.Head lift(m)	75	75
Engine	Engine model	G390	G620
	Cylinder number	single	double
	Engine type	4-stroke,air cooled, gasoline engine	
	BorexStroke(mm)	88x75	77x66
	Displacement(ml)	397	598
	Rated power(kw)	5.7	15
	Max.output power(HP)	13	20
	Rated spee(RPM)	3000	3000
	Mix.Spee(RPM)	<1300	<1300
	Fuel consumption ratio(g/kw.h)	<390	<395
	Fuel type	90#,93#,97#	
	Oil type	SAE15W-40	
	starting method	Electric start	
	Fuel tank capacity(L)	6	10
	Oil capacity(L)	1.1	1.3
Pack	Packing size(mm)	810x490x550	850x910x690
	Net weight(Kgs)	65	67
	Gross weight(Kgs)	80	90