

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## FIRE MONITOR

## PP24C Fire Monitor

PP24C Fire Monitor Service pressure: 0.5 - 1.0 Mpa Spray capacity: mixed liquids 24L/S, water 24L/S Range:  $\geq 40$  meter Horizontal rotary:  $\geq 180$  degree Max angle of elevation:  $\geq 70$  degree M...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Fire Monitor
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Fire Monitor	Model / SKU	PP24C-Fire-Monitor
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

### China PP24C Fire Monitor:

PP24C Fire Monitor

Service pressure: 0.5 - 1.0 Mpa

Spray capacity: mixed liquids 24L/S, water 24L/S

Range:  $\geq 40$  meterHorizontal rotary:  $\geq 180$  degreeMax angle of elevation:  $\geq 70$  degreeMax angle of depression:  $\leq -60$  degree

Allowable error of discharge capacity:  $\pm 8\%$

Foaming times (at 20 °C) :  $\geq 6$

25% Discharge time (at 20 °C):  $\geq 2.5\text{min}$

Effluent capacity: 85T/h(PP)

