

OTHER FIRE-FIGHTING EQUIPMENT

PQ8.0C Marine Foam Applicator

Product Description: Type:PQ8.C Rating work pressure:0.5 MPa Operation pressure:0.3-0.7 MPa Capacity of mixture liquid:400 L/min Capacity of water:400 L/min Capacity of foam:1.5 m3/min Foam range:≥15 m Water...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Other Fire-Fighting Equipment
Standard	EN
Weight / Size	Type:PQ8.C Rating work pressure:0.5 MPa Operation pressure:0.3-0.7 MPa C...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Other Fire-Fighting Equipment	Model / SKU	PQ8-0C-Marine-Foam-Applicator
Standard	EN	Weight / Size	Type:PQ8.C Rating work pressure:0.5 MPa Operation pressure:0.3-0.7 MPa Capacity of mixture liquid:400 L/min Capacity of water:400 L/min Capacity of foam:1.5 m3/min Foam range:≥15 m Water range:≥15 m Dimension:500×180×180mm Bore of gun barrel:60 mm Pipe fitting size:65 mm/ 50 mm Fluoride albumen fire-extinguishing foam Foam Liquid:20L
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

Product Description:

Type:PQ8.C

Rating work pressure:0.5 MPa

Operation pressure:0.3-0.7 MPa

Capacity of mixture liquid:400 L/min

Capacity of water:400 L/min

Capacity of foam:1.5 m³/min

Foam range:≥15 m

Water range:≥15 m

Dimension:500×180×180mm

Bore of gun barrel:60 mm

Pipe fitting size:65 mm/ 50 mm

Fluoride albumen fire-extinguishing foam

Foam Liquid:20L