

MONITORING AND ALARMING DEVICE

RDBJ-12A Intelligent Instrumentation

The instrumentation is used to monitor liquid level alarm limits, if the value exceeds the alarm value, the instrumentation emit alarm. Working voltage: DC18V ~ DC28V Input signal: switch signal (should fitted with loo...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Monitoring And Alarming Device
Standard	EN
Weight / Size	Silence, Acknowledge, Testing Overall size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Monitoring And Alarming Device	Model / SKU	RDBJ-12A-Intelligent-Instrumentation
Standard	EN	Weight / Size	Silence, Acknowledge, Testing Overall size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China RDBJ-12A Intelligent Instrumentation:

The instrumentation is used to monitor liquid level alarm limits, if the value exceeds the alarm value, the instrumentation emit alarm.

Working voltage: DC18V ~ DC28V
Input signal: switch signal (should fitted with loop failure resistance)
Max. Input channel: 12channel
Output relay: audible alarm (dry contact)
Communication interface: RS485

Output relay capacity: AC220V/2A

Function key: Silence, Acknowledge, Testing

Overall size: 75W×158H×88L (mm)

Cutout size: 75W×15 H (mm)

Powerful anti-jamming, inner self-checking function

Alarm for sensor fault

RS485 interface for telecontrol

High-luminance and double- LED for alarm indication

Approved by classification societies