

GRAB BUCKETS

Remote Control Grab

Remote Control Grab Remote control grab is an efficient tool for lodaing and unloding bulk cargo. The grab closes by lifting crane and opens by transmitter without any additional power. The hydraulic and electric ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Grab Buckets
Standard	DIN
Weight / Size	Grab opening speed can be adjusted by cargo weight, so grab opening will...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Grab Buckets	Model / SKU	Remote-Control-Grab
Standard	DIN	Weight / Size	Grab opening speed can be adjusted by cargo weight, so grab opening will not has inpect to crane and can ensure grab opening with high speed.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ Remote Control Grab

■ Specification

Remote Control Grab

Remote control grab is an efficient tool for lodaing and unloding bulk cargo. The grab closes by lifting crane and opens by transmitter without any additional power. The hydraulic and electric parts are plug-in modular design, easily maintain and repair, suitable for ship ocean voyages. The electric system and hydraulic system is water proof design, which can

prevent the grab from wave and rain washing. Each grab is tested strictly by immersed under water 24hours. Grab opening speed can be adjusted by cargo weight, so grab opening will not has impact to crane and can ensure grab opening with high speed. Grab can work for long time with low trouble rate. Fully charged battery can work more than 180 hour. Easy operation, crane does not need any other auxiliary equipment. Grab can work immediately when put on crane hook. Remote control grabs are now widely used on bulk vessels, ports, and are exported in batches.

Specification

Model	capacity(m3)	Total lifting weight(t)	Dead weight(t)	dimension(mm)						
				A	B	c	D	E	Pulley diameter(mm)	Wire rope diameter(mm)
YK10[3-6]4.5	3-6	10	4.5	2600	338	375	401	270	445	24
YK14(4-7]6	4-7	14	6	2780	338	409	448	280	520	28
YK16(4-8]7	4-8	16	7	2880	338	409	448	300	520	28
YK20[5-10]8	5-10	20	8	2880	351	409	448	300	560	32
YK25(6-12]10	6-12	25	10	3000	351	409	448	300	650	36
YK28[8-16]10.5	8-16	28	10.5	3060	351	409	448	300	650	36
YK32(10- 20] 13.5	10-20	35	14	3270	414	409	448	300	720	40
YK40(12-24]17	12-24	40	17	3520	414	409	448	300	800	45
YK50(15-30]21	15-30	50	21	4000	414	409	448	300	880	52