

NEK606 CABLE

RFOU Cable 250V Halogen-free Flame Retardant Communication Cable NEK606

ISO9001 Supplier

Class Certificate

Export Supply

Offshore Instrument & Communication Cable Types: S1 RFOU(i) Halogen-free Flame Retardant Communication Cable with Individual Screen S1/S5 RFOU(i) Halogen-free Mud-Resistant Flame Retardant Co...



Key Highlights

Category	NEK606 Cable
Standard	DIN
Material	Tinned Copper/EPR insulation/Twisted+Individual Screen/SHF2 sheath/Tinne...
Weight / Size	IEC 60092-376 NEK 606-2004 IEC 60332-3 Flame Retardant Category A IEC607...
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	NEK606 Cable	Model / SKU	RFOU-Cable-250V-Halogen-free-Flame-Retardant-Communication-Cable-NEK606
Standard	DIN	Material	Tinned Copper/EPR insulation/Twisted+Individual Screen/SHF2 sheath/Tinned Copper Wire/SHF2 or SHF Mud
Weight / Size	IEC 60092-376 NEK 606-2004 IEC 60332-3 Flame Retardant Category A IEC60754-1 Halogen-free IEC 61034-1 Low Smoke Cores & Size Cores:	Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	- China RFOU Cable 250V Halogen-free Flame Retardant Communication Cable NEK606: - Cable Construction - Cores & Size - Application:	- Types: - Standards - Feature
----------	--	--

China RFOU Cable 250V Halogen-free Flame Retardant Communication Cable NEK606:



Offshore Instrument & Communication Cable

Types:

S1 RFOU(i) Halogen-free Flame Retardant Communication Cable with Individual Screen

S1/S5 RFOU(i) Halogen-free Mud-Resistant Flame Retardant Communication Cable with Individual Screen

Cable Construction

Classification	Code	Construction details
Conductor	Tinned Annealed Stranded Copper Wire	
Insulation	R	EP Rubber
Twisting	Color coded cores twisted together for pair or triple	
Individual Screen	(i)	Each Pair/Triple are individual screened by aluminum polyester with copper wire
Bedding/Inner Covering	F	Halogen-free compound SHF1
Aarmor	O	Tinned Copper wire braided
Outer Sheath	U	Halogen-free Thermoset compound SHF2
Halogen-free mud resistant thermoset compound, SHF Mud		
Colour	Grey or Blue	

Standards

Design : IEC 60092-376

NEK 606-2004

IEC 60332-3 Flame Retardant Category A

IEC60754-1 Halogen-free

IEC 61034-1 Low Smoke

Cores & Size

Cores: 1P 2P 3P 4P 7P 8P 10P 12P 14P 16P 18P 19P 24P 32P

1T 2T 3T 4T 7T 8T 10T 12T 14T 16T 18T 19T 24T 32T

Size (sqmm): 0.75 1 1.5

Feature

Halogen-free, Low Smoke, Flame retardant, Mud Resistant

Application:

The cable is fixed installation for Instrumentation, Communication, Control and Alarm system in both explosion risk and safe area; SHF Mud for Installation in areas expose to Mud and Drilling or Cleaning fluids