

AIR BREATHING APPARATUS

RHZK6/30 SCBA

Feature: 1.SOLAS approved. 2.CCS and EC certificate available. Self contained breathing apparatus is a new model of self supporting open respirator,which is widely used in fire-fighting,chemistry industry,fi...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Air breathing apparatus
Standard	ISO
Material	Steel cylinder
Weight / Size	Model Working Pressure (MPa) Volu me (L) Air Deposit (L) Using Term (min...
Certificate	CCS or EC

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Air breathing apparatus	Model / SKU	RHZK6-30-SCBA
Standard	ISO	Material	Steel cylinder
Weight / Size	Model Working Pressure (MPa) Volu me (L) Air Deposit (L) Using Term (min) Alarm Pressure (MPa) Weight (Kg) Packing (mm) RHZK5/30 30 5 1500 40~50 4~6 ≤12 755×460×290 RHZK6/30 30 6 1800 50~60 4~6 ≤14 755×460×290 RHZK6.8/30 30 6.8 2040 50~60 4~6 ≤10 755×460×290 Type:	Certificate	CCS or EC
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- Feature:
- Condition:
- Main performance index:
- Type:

Feature:

- 1.SOLAS approved.
- 2.CCS and EC certificate available.

Self contained breathing apparatus is a new model of self supporting open respirator, which is widely used in fire-fighting, chemistry industry, fired boat, petroleum industry, smelt, mine and transportation. It is a high-performance respiratory protective device designed for fireman and special trained person when trapped in the situation with smoke, pollution and hot vapor to perform the extinguish, rescue and ambulance.

Condition:

The atmosphere is polluted by smoke, poisonous gas or/and hot vapor, or in the hypoxigen situation

In the atmosphere of -30°C~+60°C, at 0~100% relative humidity and 70kpa~125kpa atmosphere pressure.

Main performance index:

Model	Working Pressure (MPa)	Volume (L)	Air Deposit (L)	Using Term (min)	Alarm Pressure (MPa)	Weight (Kg)	Packing (mm)
RHZK5/30	30	5	1500	40~50	4~6	≤12	755×460×290
RHZK6/30	30	6	1800	50~60	4~6	≤14	755×460×290
RHZK6.8/30	30	6.8	2040	50~60	4~6	≤10	755×460×290

Type:

5 liter steel cylinder breathing apparatus and 6 liter steel cylinder breathing apparatus