

CHAIN SLING

RK02 Fireproof Eye Type Sling

Description: It uses a high-strength, high-temperature resistant aramid fiber to make a round sling with flame retardant fire resistance. The sling is light, soft, flame retardant, high temperature resistan...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|               |                                                                             |
|---------------|-----------------------------------------------------------------------------|
| Category      | Chain Sling                                                                 |
| Standard      | DIN                                                                         |
| Weight / Size | It has an ambient temperature range of -40 ° C to 180 ° C and a weight o... |
| Certificate   | CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS                       |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|             |                                                       |               |                                                                                                      |
|-------------|-------------------------------------------------------|---------------|------------------------------------------------------------------------------------------------------|
| Category    | Chain Sling                                           | Model / SKU   | RK02-Fireproof-Eye-Type-Sling                                                                        |
| Standard    | DIN                                                   | Weight / Size | It has an ambient temperature range of -40 ° C to 180 ° C and a weight of 1/2 of the ordinary sling. |
| Certificate | CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS | Warranty      | 12 Months unless specified otherwise                                                                 |
| Origin      | China                                                 |               |                                                                                                      |

CONTENTS

- Description:
- Maintenance method:
- Technical data:

## Description:



It uses a high-strength, high-temperature resistant aramid fiber to make a round sling with flame retardant fire resistance.

The sling is light, soft, flame retardant, high temperature resistant, excellent wear resistance, high strength, low elongation, large safety factor, long service life, non-conductivity, no electric shock hazard, and good resistance to chemical corrosion. Strength and other advantages.

It is suitable for use in fireworks and high temperature environments. It has an ambient temperature range of -40 ° C to 180 ° C and a weight of 1/2 of the ordinary sling.

## Maintenance method:



1. When moving the sling and cargo, do not drag it. Don't tie it up.
2. The soft ring should not be damaged with any equipment that might cause damage to it.
3. When carrying, do not screw it.
4. Slings without sheaths should not be used to carry goods with sharp corners and edges.
5. should avoid the soft ring opening angle of more than 20 °.
6. The sling should be stored in the dark and without ultraviolet radiation.
7. The sling should not be stored near an open flame or other heat source.
8. When the sling is not used, place the sling in a well-lit area.

## Technical data:

| Art.No. | Working Load Limit ( kg ) | Approx Thickness ( mm ) | Approx Width ( mm ) | Minimum length L(m) |
|---------|---------------------------|-------------------------|---------------------|---------------------|
|---------|---------------------------|-------------------------|---------------------|---------------------|

|         |       |    |     |     |
|---------|-------|----|-----|-----|
| RK02-01 | 1000  | 10 | 40  | 1.5 |
| RK02-02 | 2000  | 11 | 50  | 1.5 |
| RK02-03 | 3000  | 12 | 60  | 1.5 |
| RK02-04 | 4000  | 14 | 70  | 1.5 |
| RK02-05 | 5000  | 18 | 75  | 1.5 |
| RK02-06 | 6000  | 19 | 80  | 2   |
| RK02-08 | 8000  | 20 | 90  | 2   |
| RK02-10 | 10000 | 21 | 100 | 3   |
| RK02-12 | 12000 | 22 | 110 | 3   |
| RK02-15 | 15000 | 23 | 125 | 3   |
| RK02-20 | 20000 | 24 | 150 | 3   |