

HOT OIL TRANSFER PUMP

RY Series Air Cooled Hot Oil Pump

Type RY air-cooled hot oil pump is the energy conservation production designed and manufactured on the standard GB5662. With scientific construction and fine capacity, it is used in transporting high temperatur...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Hot Oil Transfer Pump
Standard	GB
Material	Carbon Steel, Alloy steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hot Oil Transfer Pump	Model / SKU	RY-Series-Air-Cooled-Hot-Oil-Pump
Standard	GB	Material	Carbon Steel, Alloy steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ China RY Series Air Cooled Hot Oil Pump:

■ Main Specification

China RY Series Air Cooled Hot Oil Pump:



Type RY air-cooled hot oil pump is the energy conservation production designed and manufactured on the standard GB5662.

With scientific construction and fine capacity, it is used in transporting high temperature liquid without solid particles. And the degree of corrosion resisting and working temperature is depended on the material of the main parts which connected with the medium.

Main Specification

Type	Capacity	Head	Speed	Power(kw)		Efficiency	Motor
	m3/h	m	r/min	Shaft Power	Equiped Power	η%	
15-15-100	3	10	2800	0.45	0.75	20	801
15-15-100A	2	10	2800	0.36	0.55	18	AO2-7122
15-15-100B	1	10	2800	0.2	0.37	15	AO2-7112
20-20-100	1	10	2800	0.09	0.37	26	AO2-7112
20-20-125	1.5	22	2800	0.22	0.75	30	801
40-25-160	10	28	2900	1.72	2.2	45	90L
25-25-160	3	27	2900	0.53	1.5	30	90S
32-32-160	6	28	2900	0.85	1.5	50	90S
50-32-160	12.5	30	2900	1.9	3	57	100L
50-32-200	18	40	2900	3.92	5.5	50	132SI
50-32-200A	16	32	2900	3.35	4	42	112M
50-32-250	12.5	80	2900	6.2	11	44	160MI
65-50-160	20	32	2900	3.17	5.5	55	132S1
65-40-200	30	48	2900	6.3	7.5	62	132S2

65-40-200A	25	35	2900	4	5.5	59	132S1
65-40-250	25	80	2900	10.3	15	53	160M2
65-40-250A	20	51	2900	5.67	7.5	49	132S2
65-40-315	25	125	2900	18.9	30	45	200L1
65-40-315A	22.5	100	2900	15.3	22	40	180M
80-50-200	50	50	2900	9.7	15	70	160M2
80-50-200A	45	40	2900	7.8	11	63	160M1
80-50-200B	40	32	2900	6.37	7.5	55	132S2
80-50-250	50	80	2900	17.1	22	58	180M
80-50-250A	43	60	2900	12.8	15	55	160M2
80-50-315	50	125	2900	30.4	45	56	225M
80-50-315A	45	100	2900	23.6	30	52	200L1
100-65-200	100	50	2900	18.4	22	74	180M
100-65-200A	94	44	2900	16	22	70	180M
100-65-200B	87	38	2900	13.8	15	65	160M2
100-65-200C	80	32	2900	11.8	15	59	160M2
100-65-250	100	80	2900	32.06	37	68	200L2
100-65-250A	95	72	2900	29	37	64	200L2
100-65-250B	90	65	2900	26.2	30	61	200L1
100-65-250C	85	50	2900	20.3	30	57	200L1
100-65-315	100	125	2900	50.06	75	68	280S
100-65-315A	95	113	2900	45.23	55	64.63	250M
100-65-315B	90	100	2900	40.5	55	60.5	250M

100-65-315C	82	84	2900	34.76	45	54	225M
125-100-200	200	50	2900	35.4	45	77	225M
125-100-200A	178	40	2900	26.6	37	73	200L2
125-100-250	200	70	2900	47	55	80	250M
125-100-250A	190	63	2900	41.6	55	78	250M
125-100-250B	180	57	2900	37.9	45	74	225M
125-100-250C	170	51	2900	32.15	45	72	225M
125-100-250D	150	70	2900	40	45	70	225M
150-150-200	350	50	2900	60	75	80	280S
150-150-200A	313	40	2900	45	55	76	250M
200-150-400	350	50	1450	61.8	75	78	280S
200-150-400A	330	45	1450	52.8	75	77	280S
250-200-400	500	50	1480	86.2	110	79	315S
250-200-500	500	80	1480	136	160	76.5	315M
250-200-500A	400	50	1480	75	90	73	280M