

MARINE AUTOMATIC TELEPHONE SYSTEM

SFB-6 Alarm Indicator Column

SFB-6 Alarm Indicator Column: The Alarm Indicator Column is designed for distribution of important alarms in special areas onboard ships. It includes offshore platform vision alarm and audible alarm. The audible...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Automatic Telephone System
Standard	DIN
Weight / Size	Size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Automatic Telephone System	Model / SKU	SFB-6-Alarm-Indicator-Column
Standard	DIN	Weight / Size	Size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China SFB-6 Alarm Indicator Column:

SFB-6 Alarm Indicator Column:

The Alarm Indicator Column is designed for distribution of important alarms in special areas onboard ships. It includes offshore platform vision alarm and audible alarm. The audible and visual alarm signals will be sent when the equipments with fault during operating. Then the crew or shipman will take measures against the trouble rapidly according to the signals. The systems are designed according to the rules and regulations of CCS and IMO A.1021(26). This system is widely used in varied vessels.

Main technical data:

Power supply: AC220V 50/60HZ DC24V

Alarm signals: general emergency alarm, co2 release alarm, fire alarm, machinery fault alarm, telephone call, engine telegraph etc.

Input: normally open or normally close contact without voltage.

The alarm indicator column system is comprised of relay box and alarm columns. One relay box can be connected several alarm indicator columns.

Size:

