IEC 60092 STANDARD CABLE (KOREA TYPE)

SICI/SIOI Fire Resistant Marine Telephone & Instrument Cable 250V(Non Screen)

ISO9001 Supplier

Class Certificate

Export Supply

SICI and SIOC marine telephone and instrument Cable is with the feature of Fire Resistant, produced according to IEC Standards strictly. Our cable approved by International Class Society. Cable Construct...



Key Highlights

Category	IEC 60092 Standard Cable (Korea Type)
Standard	DIN
Material	Tinned Copper/XLPE insulation/SHF1 sheath/Galvanized Steel Wire Braided/...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	IEC 60092 Standard Cable (Korea Type)	**Model / SKU**	SICI-SIOI-Fire-Resistant-Marine-Telephone-Instrument-Cable-250V-Non-Screen
Standard	DIN	**Material**	Tinned Copper/XLPE insulation/SHF1 sheath/Galvanized Steel Wire Braided/SHF1
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	**Surface**	Galvanized
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China SICI/SIOI Fire Resistant Marine Telephone & Instrument Cable 250V(Non Screen):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application

China SICI/SIOI Fire Resistant Marine Telephone & Instrument Cable 250V(Non Screen):



SICI and SIOC marine telephone and instrument Cable is with the feature of Fire Resistant, produced according to IEC Standards strictly. Our cable approved by International Class Society.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Mica Tape

Insulation : XLPE Insulation

Inner Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Galvanized Wire Braided/Tinned Copper Wire Braied

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1P, 2P,3P,4P,5P,7P,10P,12P,14P,16P,19P,20P, 24P, 30P (P:Pair)

1T, 2T,3T,4T,5T,7T,10T,12T,14T,16T,19T,20T, 24T, 30T (Triad)

Size (sqmm): 0.75, 1, 1.5, 2.5

Feature

Halogen-free, Low Smoke, Flame retardant

Application

The cable is fixed installation on ships and offshore units.