

LIFEBOAT DAVIT

Single Arm Slewing Davit

Product Description: The slewing davit is mainly used for lifting and lowering a boat/raft , and also for other types of raft davit. It have the functions of electrical(manual) hoisting, gravity lowering, hydraulic...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Lifeboat Davit
Standard	DIN
Weight / Size	Main Dimensions And Specifications:
Certificate	CCS, BV,ABS,DNV,LR,RS etc.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Lifeboat Davit	Model / SKU	Single-Arm-Slewing-Davit
Standard	DIN	Weight / Size	Main Dimensions And Specifications:
Certificate	CCS, BV,ABS,DNV,LR,RS etc.	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ Product Description:

■ Main Dimensions And Specifications:

Product Description:

The slewing davit is mainly used for lifting and lowering a boat/raft , and also for other types of raft davit. It have the functions of electrical(manual) hoisting, gravity lowering, hydraulic slewing (Oils fed from the pump station or accumulator/manual pump). It is provided with lowering and slewing functions operated from deck or remotely controlled from a position within the boat/raft. According to the arrangement of ship, the davit is of two types, right and left. Either of them is selected as per customers' demands.

Main Dimensions And Specifications:

Name	Unit	Data			
Maximum working load	KN	14	21	23	25
Slewing radius	mm	R≤5400	R≤4800	R≤5400	R≤5500
Maximum slewing load/hoisting load	KN	14			
Hoisting speed of wire rope	m/min	≥18			
Lowering speed of wire rope	m/min	40~60			
Maximum slewing angle	degree	≤330			
Stored power slewing angle	degree	≤110			
Slewing speed in stored power driven	r/min	0.6~0.8			
Slewing speed in electric power driven	r/min	≥0.25			
Diameter of wire rope	mm	16			
Capacity of drum	m	30			