

MARINE NAVIGATION SIGNAL LIGHT

Single-Deck Navigation Signal Light
CXH-1D

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.



Key Highlights

Category	Marine Navigation Signal Light
Standard	ISO
Material	Steel
Weight / Size	Voltage 24V 110V 220V Power 60W 65W 65W Lamp Holder B22d Protection Clas...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Single-Deck-Navigation-Signal-Light-CXH-1D
Standard	ISO	Material	Steel
Weight / Size	Voltage 24V 110V 220V Power 60W 65W 65W Lamp Holder B22d Protection Class IP55 Cable Diameter Dia.14-16 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-1D 3n.m 112.5o Green 4.9KGS Port Light CXH2-1D 3n.m 112.5o Red 4.9KGS Masthead Light CXH3-1D 6n.m 225o White 4.9KGS Stern Light CXH4-1D 3n.m 135o White/Yellow 4.9KGS All-round-Light CXH6-1D 3n.m 360o Red/green/white 4.9KGS	Surface	The shell is made of steel, finished by special mold-powder with the feature of corrosion-resisting and shock resistance.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China Single-Deck Navigation Signal Light CXH-1D:	■ Products Advantage:
	■ Standards:	■ Main Specification:

China Single-Deck Navigation Signal Light CXH-1D:



The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

Products Advantage:

1. Easy to install and replace with bulb.

2. The shell is made of steel, finished by special mold-powder with the feature of corrosion-resisting and shock resistance.
3. PC Material, UV resistance and non-discolouring.

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Voltage	24V	110V	220V
Power	60W	65W	65W
Lamp Holder	B22d		
Protection Class	IP55		
Cable Diameter	Dia.14-16		

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-1D	3n.m	112.5°	Green	4.9KGS
Port Light	CXH2-1D	3n.m	112.5°	Red	4.9KGS
Masthead Light	CXH3-1D	6n.m	225°	White	4.9KGS
Stern Light	CXH4-1D	3n.m	135°	White/Yellow	4.9KGS
All-round- Light	CXH6-1D	3n.m	360°	Red/green/white	4.9KGS