

MARINE NAVIGATION SIGNAL LIGHT

Single-Deck Navigation Signal Light
CXH-1P

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length50M or above as lamp signal liaison when night navigation.



Key Highlights

Category	Marine Navigation Signal Light
Standard	ISO
Material	Engineering Plastic, Steel, Stainless Steel
Weight / Size	Voltage 24V 110V 220V Power 60W 65W 65W Lamp Holder B22d Protection Clas...
Certificate	CCS Type Approval Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Single-Deck-Navigation-Signal-Light-CXH-1P
Standard	ISO	Material	Engineering Plastic, Steel, Stainless Steel
Weight / Size	Voltage 24V 110V 220V Power 60W 65W 65W Lamp Holder B22d Protection Class IP56 Cable Outside Diameter Dia.12-13 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-1P 3n.m 112.5o Green 2.6KGS Port Light CXH2-1P 3n.m 112.5o Red 2.6KGS Masthead Light CXH3-1P 3n.m 225o White 2.5KGS Stern Light CXH4-1P 3n.m 135o White/Yellow 2.7KGS All-round-Light CXH6-1P 3n.m 360o Red/green/white 2.2KGS	Certificate	CCS Type Approval Certificate
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Single-Deck Navigation Signal Light CXH-1P:	■ Product Advantage:
	■ Standards:	■ Main Specification:

China Single-Deck Navigation Signal Light CXH-1P:



The Navigation Signal Light used to the ship with length50M or above as lamp signal liaison when night navigation.

Product Advantage:

- 1. Easy to Install and replace the bulb with a leakage hole at the bottom.
- 2. The sheel is made of engineering plastic, corrosion resistance and impact resistance

3. The shade is made of polycarbonate, UV Resistance and non-discolouring color.

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Voltage	24V	110V	220V
Power	60W	65W	65W
Lamp Holder	B22d		
Protection Class	IP56		
Cable Outside Diameter	Dia.12-13		

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-1P	3n.m	112.5 ⁰	Green	2.6KGS
Port Light	CXH2-1P	3n.m	112.5 ⁰	Red	2.6KGS
Masthead Light	CXH3-1P	3n.m	225 ⁰	White	2.5KGS
Stern Light	CXH4-1P	3n.m	135 ⁰	White/Yellow	2.7KGS
All-round- Light	CXH6-1P	3n.m	360 ⁰	Red/green/white	2.2KGS