

MARINE EXPANSION JOINT

Sliding Type Expansion Joint

The product is suitable to for ship bilge water, ballast water, fresh water, sea water, fire water and oil transfer pipelines, the medium temperature≤170°C. Products standard: GB/T12465-2002, CBM1129-82 Working pressure...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Expansion Joint
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Expansion Joint	Model / SKU	Sliding-Type-Expansion-Joint
Standard	DIN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Sliding Type Expansion Joint:
- Sliding Type Expansion Joint(CB/T12465-2002) Main Specifications
- Sliding Type Expansion Joint(CBM1129-82) Main Specifications

China Sliding Type Expansion Joint:

The product is suitable to for ship bilge water, ballast water, fresh water, sea water, fire water and oil transfer pipelines, the medium temperature≤170°C.

Products standard: GB/T12465-2002, CBM1129-82

Working pressure: 1.0MPa -1.6MPa

Sliding Type Expansion Joint(CB/T12465-2002) Main Specifications

Model	DN	DW	A	B	C	D	△L	L1	Working pressure
STL-65	65	76	155	180	76	230	90	67.5	1.6
STL-80	80	89	165	180	89	230	90	67.5	1.6
STL-100	100	114	195	180	114	235	90	67.5	1.6
STL-125	125	140	225	180	140	235	90	67.5	1.6
STL-150	150	168	255	185	168	235	90	67.5	1.6
STL-200	200	219	310	185	219	250	90	67.5	1.0
STL-250	250	273	375	185	273	250	90	67.5	1.0
STL-300	300	325	440	220	325	290	110	82.5	1.0
STL-350	350	377	490	220	377	290	110	82.5	1.0
STL-400	400	426	540	220	426	290	110	82.5	1.0
STL-450	450	480	590	220	480	290	110	82.5	1.0
STL-500	500	508	625	220	506	310	110	82.5	1.0
STL-600	600	630	750	220	630	310	110	82.5	1.0

Sliding Type Expansion Joint(CBM1129-82) Main Specifications

Model	DN	DW	A	B	C	D	△L	L1	Working pressure
STL-65	65	76	190	160	75	215	90	57.5	1.6
STL-80	80	89	205	180	89	215	90	67.5	1.6
STL-100	100	114	230	180	114	215	90	67.5	1.6
STL-125	125	140	255	190	140	225	90	72.5	1.6
STL-150	150	168	285	190	168	225	90	72.5	1.6
STL-200	200	219	345	210	219	250	100	80	1.0
STL-250	250	273	410	210	273	265	100	80	1.0
STL-300	300	325	460	210	325	265	100	80	1.0
STL-350	350	377	520	240	377	300	100	95	1.0
STL-400	400	426	570	240	426	300	100	95	1.0
STL-500	500	530	652	260	508	320	100	105	1.0
STL-600	600	630	770	260	630	320	100	105	1.0