

MARINE TOOLS

Split Hydraulic Puller

Split Hydraulic Puller The hydraulic puller moves directly forward with the hydraulic starting rod, so the push rod itself does not rotate. The hook seat can be adjusted forward and backward directly wit...

ISO9001 Supplier

Class Certificate

Export Supply



jinbomarine.com

Key Highlights

Category	Marine Tools
Standard	DIN
Weight / Size	Model DYF-5 DYF-10 DYF-20 DYF-30 DYF-50 DYF-100 Safe weight(T) 5...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Tools	Model / SKU	Split-Hydraulic-Puller
Standard	DIN	Weight / Size	Model DYF-5 DYF-10 DYF-20 DYF-30 DYF-50 DYF-100 Safe weight(T) 5 10 20 30 50 100 Stroke(mm) 60 60 60 60 60 100 Three-jaw adjustment range(mm) 50-250 50-300 100-450 150-500 200-550 250-600 Working pressure(MPa) 40 63 63 63 63 63
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China Split Hydraulic Puller:

Split Hydraulic Puller

The hydraulic puller moves directly forward with the hydraulic starting rod, so the push rod itself does not rotate. The hook seat can be adjusted forward and backward directly with the thread. During operation, as long as the handle swings back and forth slightly, the hydraulic starter rod moves forward, and the hook correspondingly retreats to pull out the pulled object.

Model	DYF-5	DYF-10	DYF-20	DYF-30	DYF-50	DYF-100
Safe weight(T)	5	10	20	30	50	100
Stroke(mm)	60	60	60	60	60	100
Three-jaw adjustment range(mm)	50-250	50-300	100-450	150-500	200-550	250-600
Working pressure(MPa)	40	63	63	63	63	63