

HIGH PRESSURE PUMP

Standard Tension Jack

Standard Tension Jack      Model TCapacity mmmiddlehole  
mmOutsidedia mmCylinderboredia mmStroke pistonrod cm<sup>2</sup>Area pressure ToolAnchor  
limitplate YCW-60 60 58 1...

ISO9001 Supplier

Class Certificate

Export Supply



jinbomarine.com

Key Highlights

|             |                                            |
|-------------|--------------------------------------------|
| Category    | High Pressure Pump                         |
| Standard    | EN                                         |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|          |                                      |             |                                            |
|----------|--------------------------------------|-------------|--------------------------------------------|
| Category | High Pressure Pump                   | Model / SKU | Standard-Tension-Jack                      |
| Standard | EN                                   | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| Warranty | 12 Months unless specified otherwise | Origin      | China                                      |

China Standard Tension Jack:

Standard Tension Jack

| Model   | T Capacity | mm middle hole | mm Outside dia | mm Cylinder boredia | mm Stroke | piston rod | cm <sup>2</sup> Area | pressure | Tool Anchor | limit plate |
|---------|------------|----------------|----------------|---------------------|-----------|------------|----------------------|----------|-------------|-------------|
| YCW-60  | 60         | 58             | 180            | 140                 | 200       | 110        | 10362                | 57.9     | 90          | 100         |
| YCW-80  | 80         | 67             | 200            | 160                 | 200       | 125        | 13737.5              | 58.23    | 100         | 123         |
| YCW-100 | 100        | 78             | 230            | 180                 | 200       | 140        | 17584                | 56.86    | 118         | 128         |

|         |     |     |     |     |     |     |         |       |     |     |
|---------|-----|-----|-----|-----|-----|-----|---------|-------|-----|-----|
| YCW-120 | 120 | 78  | 245 | 200 | 200 | 150 | 23550   | 50.95 | 118 | 128 |
| YCW-150 | 150 | 100 | 270 | 220 | 200 | 170 | 24727.5 | 60.66 | 148 | 158 |
| YCW-200 | 200 | 120 | 325 | 270 | 200 | 200 | 37130.5 | 53.86 | 168 | 178 |
| YCW-250 | 250 | 130 | 350 | 290 | 200 | 220 | 43332   | 57.69 | 184 | 194 |
| YCW-300 | 300 | 146 | 380 | 320 | 200 | 260 | 54950   | 54.59 | 214 | 214 |
| YCW-350 | 350 | 165 | 400 | 340 | 200 | 260 | 59346   | 58.97 | 238 | 238 |
| YCW-400 | 400 | 165 | 450 | 360 | 200 | 270 | 70336   | 56.86 | 248 | 248 |
| YCW-450 | 450 | 175 | 480 | 380 | 200 | 280 | 78735.5 | 57.15 | 248 | 248 |
| YCW-500 | 500 | 196 | 500 | 400 | 200 | 300 | 84.73.5 | 59.47 | 278 | 289 |
| YCW-650 | 650 | 240 | 600 | 480 | 200 | 360 | 119320  | 54.47 | 318 | 338 |