

AIR AND GENERAL PURPOSE HOSE

Steam Hose

Used steam, saturated water High Temperature, Aging, Weather Resistance Working Temperature: -20 TO 150 °C Safety Factor: 1:3 Hose Lining: EPDM ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Air and General Purpose Hose
Standard	DIN
Material	EPDM
Weight / Size	EPDM Main Specification ID OD WP BP Bending Radius Plies Weight Length m...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Air and General Purpose Hose	Model / SKU	Steam-Hose
Standard	DIN	Material	EPDM
Weight / Size	EPDM Main Specification ID OD WP BP Bending Radius Plies Weight Length mm inch mm inch Mpa bar Mpa bar mm B kg/m m 12.5 1/2" 25 1" 1 10 3 30 180 2 0.8 20-50 16 5/8" 29 1-1/4" 1 10 3 30 210 2 1 20-50 19 3/4" 32 1-1/4" 1 10 3 30 240 2 1.1 20-50 22 7/8" 34 1-2/5" 1 10 3 30 280 2 1.2 20-50 25 1" 38 1-1/2" 1 10 3 30 375 2 1.5 20-50 31.5 1-1/4" 46 2" 0.8 8 2.4 24 420 3 1.8 20-50 38 1-3/5" 52 2" 0.8 8 2.4 24 500 3 2 20-50 45 1-3/4" 60 2-1/2" 0.8 8 2.4 24 610 3 2.2 20-50 51 2" 65 2-1/2" 0.8 8 2.4 24 630 3 2.5 20-50 57 2- 1/4" 72 2-4/5" 0.8 8 2.4 24 850 3 2.8 20-50	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Steam Hose:	■ Main Specification
----------	---------------------	----------------------

China Steam Hose:

- Used steam, saturated water
- High Temperature, Aging, Weather Resistance
- Working Temperature: -20 TO 150 °C
- Safety Factory: 1:3
- Hose Lining: EPDM
- Reinforcement Layer: Tire Cord with Helix Wire
- Cover Rubber Layer: EPDM

Main Specification

ID		OD		WP		BP		Bending Radius	Plies	Weight	Length
mm	inch	mm	inch	Mpa	bar	Mpa	bar	mm	B	kg/m	m
12.5	1/2"	25	1"	1	10	3	30	180	2	0.8	20-50
16	5/8"	29	1-1/4"	1	10	3	30	210	2	1	20-50

19	3/4"	32	1-1/4"	1	10	3	30	240	2	1.1	20-50
22	7/8"	34	1-2/5"	1	10	3	30	280	2	1.2	20-50
25	1"	38	1-1/2"	1	10	3	30	375	2	1.5	20-50
31.5	1-1/4"	46	2"	0.8	8	2.4	24	420	3	1.8	20-50
38	1-3/5"	52	2"	0.8	8	2.4	24	500	3	2	20-50
45	1-3/4"	60	2-1/2"	0.8	8	2.4	24	610	3	2.2	20-50
51	2"	65	2-1/2"	0.8	8	2.4	24	630	3	2.5	20-50
57	2-1/4"	72	2-4/5"	0.8	8	2.4	24	850	3	2.8	20-50