

MARINE EXPANSION JOINT

Stuffing Box Type Expansion Joint

Stuffing box type expansion joints applies to the connection of thermal steam pipeline, by tighten the nut, the gland presses the sealing ring and packing to sick close the expansion pipe to assure leak-prove, the expans...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Expansion Joint
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Expansion Joint	Model / SKU	Stuffing-Box-Type-Expansion-Joint
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China


CONTENTS

- China Stuffing Box Type Expansion Joint:
- Stuffing Box Type Expansion Joint Main Specifications

China Stuffing Box Type Expansion Joint:

Stuffing box type expansion joints applies to the connection of thermal steam pipeline, by tighten the nut, the gland presses the sealing ring and packing to sick close the expansion pipe to assure leak-prove, the expansion pipe can freely expand or contract when temperature changes and compensation thus achieved.

序号 No	名称 Name	数量 Quantity	材料 Material
1	本体 Body	1	Q235、20、304
2	密封圈 Sealing ring	5	PTFE、柔性石墨(Goat Graphite)
3	压盖 Follower	1	Q235、ZG230、35、304
4	螺栓 Bolt	n	Q235、35、316L、304
5	螺母 Nut	2n	Q235、20、316L、304
6	伸缩管 Expansion Pipe	1	Q235、20、304



Stuffing Box Type Expansion Joint Main Specifications

DN	L	ΔL	Flange					
			0.6MPa		1.0 MPa		1.6MPa	
			D	D1	D	D1	D	D1
50	310	100	165	125	165	125	165	125
65			185	145	185	145	185	145
80	330		200	160	200	160	200	160
100	360		220	180	220	180	220	180
125			250	210	250	210	250	210
150	380		285	240	285	240	285	240
200	395		340	295	340	295	340	295
250	420		395	350	395	350	405	350
300			445	400	445	400	460	400
350	430		505	460	505	460	520	460
400			565	515	565	515	580	515
450	450		615	565	615	565	640	565
500	500		670	620	670	620	715	650