

FILTER

SZL25 Model Double-Cylinder Paper Filter

ISO9001 Supplier

Class Certificate

Export Supply

SZL25 Model Double-Cylinder Paper Filter The filter model representation is as follows:
SZL → SBL represent the double berrelled 65 → 200 representations passes diameters 200mm
Work pressure ...

Loading product image...

Key Highlights

Category	Filter
Standard	ISO
Weight / Size	SZL → SBL represent the double berrelled 65 → 200 representations passes dia...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Filter	Model / SKU	SZL25-Model-Double-Cylinder-Paper-Filter
Standard	ISO	Weight / Size	SZL → SBL represent the double berrelled 65 → 200 representations passes diameters 200mm Work pressure Flow Safe filter cylinder precision Normal using precision Pressure difference of safe value opening Pressure difference of by-pass valve opening 0.06Mpa 2x25m³/h 60um 10-15um 0.2±0.02Mpa 0.4±0.02Mpa SZL25 Model Double-Cylinder Paper Filter Technical Parameters: Model Current capacity(referencem³/h) Passes the diameter and the joint size(mm) External dimensions(mm) Installing size(mm) Weight(kg) DN K E R r 4-M1 H1 H2 L φ N P W V Y Z 4-M2 SZL20 0.5-1.5 20 60 50 22 12 10 320 60 95 85 193 184 100 53 75 35 10 8 SZL25 1.5-2 25 62 55 25 12 10 375 77 110 98 216 206 100 70 80 40 10 3 SZL25 2-4 32 75 70 35 15 12 420 90 130 125 264 226 120 80 90 40 12 19 SZL25 4-6 40 75 70 35 15 12 445 90 130 125 264 226 120 80 90 40 12 22 DN D D1 E N-M1 H1 L N P Y Z N-D SZL65A I 25-50 65 184 145 190 8-M16 597 220 510 268 474 320 4-φ14 SZL65A II 40-80 65 184 145 190 8-M16 780 220 510 268 474 320 4-φ14
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	SZL25 Model Double-Cylinder Paper Filter SZL25 Model Double-Cylinder Paper Filter Technical Parameters:
----------	---

SZL25 Model Double-Cylinder Paper Filter

The filter model representation is as follows:
SZL → SBL represent the double berrelled
65 → 200 representations passes diameters 200mm

Work pressure	Flow	Safe filter cylinder precision	Normal using precison	Pressure difference of safe value opening	Pressure difference of by-pass valve opening
0.06Mpa	2x25m³/h	60um	10-15um	0.2±0.02Mpa	0.4±0.02Mpa

SZL25 Model Double-Cylinder Paper Filter Technical Parameters:

Model	Current capacity (referen cem³/h)		Passes the diameter and the joint size(mm)					External dimensions(mm)							Installing size(mm)				Wei ght(kg)	
			D N	K	E	R	r	4- M1	H1	H 2	L	φ	N	P	W	V	Y	Z		4- M2
SZL20	0.5-1.5		20	60	50	22	1 2	10	32 0	60	95	85	19 3	18 4	10 0	5 3	7 5	3 5	10	8
SZL25	1.5-2		25	62	55	25	1 2	10	37 5	77	11 0	98	21 6	20 6	10 0	7 0	8 0	4 0	10	3
SZL25	2-4		32	75	70	35	1 5	12	42 0	90	13 0	12 5	26 4	22 6	12 0	8 0	9 0	4 0	12	19
SZL25	4-6		40	75	70	35	1 5	12	44 5	90	13 0	12 5	26 4	22 6	12 0	8 0	9 0	4 0	12	22
DN	D	D1	E	N-M1		H1		L	N		P		Y	Z	N-D					
SZL65A I	25-50		65	18 4	14 5	19 0	8-M16		597		22 0	510		268		4 7 4	3 2 0	4-φ14		
SZL65A II	40-80		65	18 4	14 5	19 0	8-M16		780		22 0	510		268		4 7 4	3 2 0	4-φ14		