

MARINE COMPASS

TS-630 Marine Three-Arm Protractor

Usage: 1.Marine three-arm protractor cooperates with sextant to measure the marine position
2.Threepoint-two-angle method to measure the marine position on the chart
Structure: Thr...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Compass
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Compass	Model / SKU	TS-630-Marine-Three-Arm-Protractor
Standard	DIN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ Usage:

■ Structure:

Usage:

- 1.Marine three-arm protractor cooperates with sextant to measure the marine position
- 2.Threepoint-two-angle method to measure the marine position on the chart

Structure:

Three-arm protractor consists of cupreous graduated circle(180 degrees on the left and right), 3 surveyor's poles(fixed pole in the center and movable pole on the left and right), micro drum wheel and indicators, needle in the center and worm gear screw rod, etc.

Model	TS-630
Diameter of the graduated circle	126.8mm
Arm length	340mm
Length of connecting arm	290mm
Total length of the pointing arm	630mm
Minimal reading number	1min
Other	differential drum type