

IEC 60092 STANDARD CABLE (KOREA TYPE)

TXXI(c) Flame Retardant Marine Telephone Cable 250V (Light Weight Cable)

ISO9001 Supplier

Class Certificate

Export Supply

TXXI(c) Flame Retardant Marine Telephone and Instrument Cable are collective screened by Aluminum Polyester with copper wire, 150/250V



Key Highlights

Category	IEC 60092 Standard Cable (Korea Type)
Standard	EN
Material	Tinned Copper/XLPE insulation/SHF1 Outer Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (Korea Type)	Model / SKU	TXXI-c-Flame-Retardant-Marine-Telephone-Cable-250V-Light-Weight-Cable
Standard	EN	Material	Tinned Copper/XLPE insulation/SHF1 Outer Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China TXXI(c) Flame Retardant Marine Telephone Cable 250V (Light Weight Cable):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application

China TXXI(c) Flame Retardant Marine Telephone Cable 250V (Light Weight Cable):



TXXI(c) Flame Retardant Marine Telephone and Instrument Cable are collective screened by Aluminum Polyester with copper wire, 150/250V

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : XLPE Insulation

Collective Screen: Pair/Triad laid up and collective screened by aluminum polyester tape with copper wire

Inner Covering: None

Armour : None

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1P, 2P,3P,4P,5P,7P,10P,12P,14P,16P,19P,20P, 24P, 30P (P:Pair)

1T, 2T,3T,4T,5T,7T,10T,12T,14T,16T,19T,20T, 24T, 30T (Triad)

Size (sqmm): 0.75, 1, 1.5, 2.5

Feature

Halogen-free, Low Smoke, Flame retardant

Application

The cable is fixed installation on ships and offshore units, used for telephone and instrument.