

WALL PANEL

Type A Perforated Sound Reduction Panel

ISO9001 Supplier

Class Certificate

Export Supply

Type A Perforated Sound Reduction Panel: Fireproof Class: B15 Thickness: 25mm Size: Max 3000mm length, 600/550mm width Weight: 13.6kg/m2 Sound Absorption Coefficient: NRC=0.65 Thermal ...



Key Highlights

Category	Wall Panel
Standard	EN
Material	Rock Wool
Weight / Size	25mm Size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Wall Panel	Model / SKU	Type-A-Perforated-Sound-Reduction-Panel
Standard	EN	Material	Rock Wool
Weight / Size	25mm Size:	Surface	galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

Type A Perforated Sound Reduction Panel:

Fireproof Class: B15

Thickness: 25mm

Size: Max 3000mm length, 600/550mm width

Weight: 13.6kg/m2

Sound Absorption Coefficient: $NRC=0.65$

Thermal Transittance: $0.92Kcal/m^2h^{\circ}C$

Surface Finish: PVC PET/HK-3 Film or galvanized steel plate

Core Material: Rock Wool

Tolerance: Width $0\sim-1$, Height: ± 3 , Thickness: $0\sim-1$