

WALL PANEL

Type C Wall Panel

Type C Wall Panel Model Thickness Fire class Core material B100C 100MM A-6...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Wall Panel
Standard	EN
Material	Galvanized/ Stainless steel plate with PVC film and rock wool
Weight / Size	Type C Wall Panel Model Thickness Fire class Core material B100C 100MM A...
Certificate	ABS, LR, BV, GL, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Wall Panel	Model / SKU	Type-C-Wall-Panel
Standard	EN	Material	Galvanized/ Stainless steel plate with PVC film and rock wool
Weight / Size	Type C Wall Panel Model Thickness Fire class Core material B100C 100MM A-60 rock wool B50C 50mm B-15 rock wool B30C 30mm B-15 rock wool B25C 25mm B-0 rock wool B25C 25mm B-0 Aluminum honeycomb SB25C ≥75mm B-30/B-15 rock wool B50CD 50mm B-15 rock wool B50CGa 50mm B-15 rock wool Main Specification Type B100C B50C B30C Fire class A-60 B-15 B-15 Weight 24.8kg/m2 16.1kg/m2 13.7kg/m2 Sound reduction 32dB 33dB --dB Thermal transmittance 0.33Kcal/m2h°C 0.58Kcal/m2h°C 0.93Kcal/m2h°C Core material Rock wool 150kg/m3 Surface finish PVC film(150μ,low flame spread) or galvanized steel Dimension 30/50/100mm(t)×550mm(w)×length (max.3500mm) Tolerances Thickness0-1×Width0-1×Length±3	Surface	galvanized
Certificate	ABS, LR, BV, GL, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ Type C Wall Panel	■ Main Specification
----------	---------------------	----------------------



Type C Wall Panel

Model	Thickness	Fire class	Core material
B100C	100MM	A-60	rock wool
B50C	50mm	B-15	rock wool
B30C	30mm	B-15	rock wool
B25C	25mm	B-0	rock wool
B25C	25mm	B-0	Aluminum honeycomb
SB25C	≥75mm	B-30/B-15	rock wool
B50CD	50mm	B-15	rock wool
B50CGa	50mm	B-15	rock wool

Main Specification

Type	B100C	B50C	B30C
Fire class	A-60	B-15	B-15
Weight	24.8kg/m ²	16.1kg/m ²	13.7kg/m ²
Sound reduction	32dB	33dB	--dB
Thermal transmittance	0.33Kcal/m ² h°C	0.58Kcal/m ² h°C	0.93Kcal/m ² h°C
Core material	Rock wool 150kg/m ³		
Surface finish	PVC film(150μ, low flame spread) or galvanized steel		
Dimension	30/50/100mm(t)×550mm(w)×length (max.3500mm)		
Tolerances	Thickness0-1×Width0-1×Length±3		