

SHACKLE

Type H10 Bow Safety Pin Shackle

Material : Alloy steel Safety factor : 5 times Standards : Generally according to US Federal Spec RR-C-271 Finish : Painted Temperature range : -40°C up to +200°C, Polar Rated ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Shackle
Standard	DIN
Material	Grade R3/R3S/R4/R4S/R5
Weight / Size	120Ton to 2000Ton
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Shackle	Model / SKU	Type-H10-Bow-Safety-Pin-Shackle
Standard	DIN	Material	Grade R3/R3S/R4/R4S/R5
Weight / Size	120Ton to 2000Ton	Surface	Painted
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China Type H10 Bow Safety Pin Shackle:

Material : Alloy steel

Safety factor : 5 times

Standards : Generally according to US Federal Spec RR-C-271

Finish : Painted Temperature range : -40°C up to +200°C, Polar Rated

Standard certification : Certificate of Conformity 3.1 material certificate EN 1020

WLL:120Ton to 2000Ton.

Shackles from WLL 1250 ton completed with eyebolts on both sides.

