

MARINE STOCKLESS ANCHOR

Type M SPEK Anchor

Type M Spek Anchor M Type SPEK Anchor is the improved anchor with lower point of gravity based on hall anchor, Anchor fluke grounded easily, more stability, when SPEK Anchor haul up, anchor fluke will tur...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Stockless Anchor
Standard	EN
Material	Casting Steel
Weight / Size	80KGS to 20000KGS
Certificate	ABS, LR, BV, DNV, GL, RINA, NK, KR, RS, IRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Stockless Anchor	Model / SKU	Type-M-SPEK-Anchor
Standard	EN	Material	Casting Steel
Weight / Size	80KGS to 20000KGS	Certificate	ABS, LR, BV, DNV, GL, RINA, NK, KR, RS, IRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Type M SPEK Anchor:
 - Anchor SPEK Type M Size:
- M SPEK Anchor Specification:
 - Type M SPEK Anchor Photo

China Type M SPEK Anchor:

Type M Spek Anchor

M Type SPEK Anchor is the improved anchor with lower point of gravity based on hall anchor, Anchor fluke grounded easily, more stability, when SPEK Anchor haul up, anchor fluke will turn over against the hull, which would not make damage to ship hull.

All anchors could be supplied with LR, ABS, BV, GL, DNV, KR, NK, IRS and CCS Certificate, please intimate when you inquiry.

M SPEK Anchor Specification:

Material: Casting Steel

Weight: 80KGS to 20000KGS

Class Certificate: ABS, LR, BV, DNV, GL, NK, KR, IRS and CCS

Anchor SPEK Type M Size:

Nominal Weight (KG)	Size(mm)					
	A	B	C	D	E	H
80	339	468	108	611	336	222
105	371	512	120	669	336	242
135	371	512	149	669	368	254
180	445	613	142	800	440	290
240	445	613	182	800	440	304
300	527	727	168	949	522	344
360	527	727	190	949	522	358
420	590	813	188	1062	584	385
480	590	813	211	1062	584	395
570	652	900	208	1175	647	428
660	653	900	236	1175	647	438
780	725	1000	231	1305	718	473
900	725	1000	264	1215	718	485
1020	793	1093	252	1428	785	518
1140	793	1093	277	1428	785	530
1290	858	1183	273	1544	850	561
1440	858	1183	299	1544	850	573
1590	920	1268	293	1655	911	604
1740	920	1268	315	1655	911	611
1920	980	1350	312	1761	970	640
2100	980	1350	337	1761	970	650
2280	1038	1430	331	1866	1027	678
2460	1038	1430	355	1866	1027	688
2640	1090	1500	347	1959	1079	712

2850	1190	1500	380	1950	1079	722
3060	1144	1578	365	2058	1133	748
3300	1144	1578	387	2058	1133	760
3540	1202	1656	383	2159	1189	785
3780	1202	1656	405	2159	1189	787
4050	1257	1732	400	2258	1244	821
4320	1257	1732	422	2258	1244	831
4590	1257	1732	444	2258	1244	841
4890	1338	1846	426	2405	1325	874
5250	1338	1846	450	2405	1325	888
5610	1432	1974	431	2405	1418	936
6000	1432	1974	457	2577	1418	936
6450	1432	1974	483	2577	1418	950
6900	1533	2112	462	2757	1518	1001
7350	1533	2112	488	2757	1518	1001
7800	1533	2112	514	2757	1518	1015
8300	1621	2234	489	296	1605	1059
8700	1621	2234	517	2916	1605	1059
9300	1621	2234	545	2916	1605	1074
9900	1726	2380	520	3015	1709	1128
10500	1726	2380	550	3105	1709	1128
11100	1726	2380	580	3105	1709	1138
11700	1819	2507	554	3273	1701	1188
12300	1819	2507	580	3273	1701	1188
12900	1819	2507	607	3273	1701	1200
13500	1904	2624	577	3425	1885	1243
14100	1904	2624	607	3425	1885	1243
14700	1904	2624	650	3425	1885	1243
15400	1904	2782	657	3425	1885	1263
16100	2018	2782	612	3632	1998	1318
16900	2018	2782	638	3632	1998	1318
17800	2018	2782	683	3632	1998	1318
18800	2018	2782	699	3632	1998	1343

20000	2170	2990	652	3905	2148	1416
-------	------	------	-----	------	------	------

Type M SPEK Anchor Photo



11100KGS M SPEK Anchor



Other SPEK Anchor:

[Type SR SPEK Anchor](#)

[95 SPEK Anchor](#)