

WALL PANEL

Type M Wall Panel

Type M Wall Panel Model Thickness Fire class Core material B50M 50MM B-15 ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Wall Panel
Standard	EN
Material	Galvanized/ Stainless steel plate with PVC film and rock wool
Weight / Size	Type M Wall Panel Model Thickness Fire class Core material B50M 50MM B-1...
Certificate	CCS, LLOYDS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Wall Panel	Model / SKU	Type-M-Wall-Panel
Standard	EN	Material	Galvanized/ Stainless steel plate with PVC film and rock wool
Weight / Size	Type M Wall Panel Model Thickness Fire class Core material B50M 50MM B-15 rock wool B25M 25mm B-15 rock wool B50M(II) 50mm B-30/B-15 rock wool B25M(II) 25mm B-15 rock wool B50MD(II) 50mm B-30/B-15 rock wool B50MD 50mm B-15 rock wool B50MG 50mm B-15 rock wool Main Specification Type B25M B50M Fire class B-15 B-15 Weight 15.0kg/m2 18.6kg/m2 Sound reduction --dB --dB Thermal transmittance 1.13Kcal/m2h°C 0.58Kcal/m2h°C Core material Rock wool 150kg/m3 Surface finish PVC film(150μ,low flame spread) or galvanized steel Dimension 25/50mm(t)×550mm(w)×length (max.3500mm) Tolerances Thickness0-1×Width0-1×Length±3	Surface	galvanized
Certificate	CCS, LLoyds	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ Type M Wall Panel	■ Main Specification
----------	---------------------	----------------------



Type M Wall Panel

Model	Thickness	Fire class	Core material
B50M	50MM	B-15	rock wool
B25M	25mm	B-15	rock wool
B50M(II)	50mm	B-30/B-15	rock wool
B25M(II)	25mm	B-15	rock wool
B50MD(II)	50mm	B-30/B-15	rock wool
B50MD	50mm	B-15	rock wool
B50MG	50mm	B-15	rock wool

Main Specification

Type	B25M	B50M
Fire class	B-15	B-15
Weight	15.0kg/m2	18.6kg/m2
Sound reduction	--dB	--dB
Thermal transmittance	1.13Kcal/m2h°C	0.58Kcal/m2h°C
Core material	Rock wool 150kg/m3	
Surface finish	PVC film(150μ,low flame spread) or galvanized steel	
Dimension	25/50mm(t)×550mm(w)×length (max.3500mm)	
Tolerances	Thickness0-1×Width0-1×Length±3	