

PERSONAL TRANSFER BASKET

Vertical Type Personal Transfer Basket

We have vertical type personal transfer basket and horizontal type peronsal transfer basket available. Popular type is horizontal type personal transfer basket . The volume of vertical type is very big ,the t...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Personal Transfer Basket
Standard	EN
Material	Horizontal Type Model Height Chassis diameter Allowable Person Safe work...
Weight / Size	Horizontal Type Model Height Chassis diameter Allowable Person Safe work...
Certificate	CE, ABS and KR .

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Personal Transfer Basket	Model / SKU	Vertical-Type-Personal-Transfer-Basket
Standard	EN	Material	Horizontal Type Model Height Chassis diameter Allowable Person Safe working load (KG) buoyancy (person) Sling material Weight (KG) Volume HY-4 6320 1420 4 380 2 Stainless Steel Wire Rope 70 0.45 HY-6 10050 1600 6 570 3 Stainless Steel Wire Rope 95 0.65 HY-10 10050 1860 10 950 5 Stainless Steel Wire Rope 100 0.8 HY-18 10050 2500 18 1700 9 Stainless Steel Wire Rope 150 1.6 HY-(II)-4 6320 1400 4 380 2 High strength polypropylene 80 0.65 HY-(II)-6 10050 1600 6 570 3 High strength polypropylene 100 0.85 HY-(II)-10 10050 1640 10 950 10 High strength polypropylene 120 1 Vertical Type HYL-4 6320 1420 4 380 _ Stainless Steel Wire Rope 250 5.5 HYL-6 6320 1600 6 570 _ Stainless Steel Wire Rope 280 6.5 HYL-10 6320 1640 10 950 _ Stainless Steel Wire Rope 290 7 HYL-12 6320 1800 12 1140 _ Stainless Steel Wire Rope 360 9.2

Weight / Size	Horizontal Type Model Height Chassis diameter Allowable Person Safe working load (KG) buoyancy (person) Sling material Weight (KG) Volume HY-4 6320 1420 4 380 2 Stainless Steel Wire Rope 70 0.45 HY-6 10050 1600 6 570 3 Stainless Steel Wire Rope 95 0.65 HY-10 10050 1860 10 950 5 Stainless Steel Wire Rope 100 0.8 HY-18 10050 2500 18 1700 9 Stainless Steel Wire Rope 150 1.6 HY-(II)-4 6320 1400 4 380 2 High strength polypropylene 80 0.65 HY-(II)-6 10050 1600 6 570 3 High strength polypropylene 100 0.85 HY-(II)-10 10050 1640 10 950 10 High strength polypropylene 120 1 Vertical Type HYL-4 6320 1420 4 380 _ Stainless Steel Wire Rope 250 5.5 HYL-6 6320 1600 6 570 _ Stainless Steel Wire Rope 280 6.5 HYL-10 6320 1640 10 950 _ Stainless Steel Wire Rope 290 7 HYL-12 6320 1800 12 1140 _ Stainless Steel Wire Rope 360 9.2	Certificate	CE, ABS and KR .
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ China Vertical Type Personal Transfer Basket:

■ Technical Data: Horizontal Type Model Height Chassis diameter Allowable Person Safe working load (KG) buoyancy (person) Sling material Weight (KG) Volume HY-4 6320 1420 4 380 2 Stainless Steel Wire Rope 70 0.45 HY-6 10050 1600 6 570 3 Stainless Steel Wire Rope 95 0.65 HY-10 10050 1860 10 950 5 Stainless Steel Wire Rope 100 0.8 HY-18 10050 2500 18 1700 9 Stainless Steel Wire Rope 150 1.6 HY-(II)-4 6320 1400 4 380 2 High strength polypropylene 80 0.65 HY-(II)-6 10050 1600 6 570 3 High strength polypropylene 100 0.85 HY-(II)-10 10050 1640 10 950 10 High strength polypropylene 120 1 Vertical Type HYL-4 6320 1420 4 380 _ Stainless Steel Wire Rope 250 5.5 HYL-6 6320 1600 6 570 _ Stainless Steel Wire Rope 280 6.5 HYL-10 6320 1640 10 950 _ Stainless Steel Wire Rope 290 7 HYL-12 6320 1800 12 1140 _ Stainless Steel Wire Rope 360 9.2

China Vertical Type Personal Transfer Basket:

We have vertical type personal transfer basket and horizontal type personal transfer basket available.

Popular type is horizontal type personal transfer basket .

The volume of vertical type is very big ,the transportation cost is high.

Technical Data:

Horizontal Type	Model	Height	Chassis diameter	Allowable Person	Safe working load (KG)	buoyancy (person)	Sling material	Weight (KG)	Volume
	HY-4	6320	1420	4	380	2	Stainless Steel Wire Rope	70	0.45
	HY-6	10050	1600	6	570	3	Stainless Steel Wire Rope	95	0.65
	HY-10	10050	1860	10	950	5	Stainless Steel Wire Rope	100	0.8
	HY-18	10050	2500	18	1700	9	Stainless Steel Wire Rope	150	1.6
	HY-(II)-4	6320	1400	4	380	2	High strength polypropylene	80	0.65
	HY-(II)-6	10050	1600	6	570	3	High strength polypropylene	100	0.85
	HY-(II)-10	10050	1640	10	950	10	High strength polypropylene	120	1
Vertical Type	HYL-4	6320	1420	4	380	—	Stainless Steel Wire Rope	250	5.5
	HYL-6	6320	1600	6	570	—	Stainless Steel Wire Rope	280	6.5
	HYL-10	6320	1640	10	950	—	Stainless Steel Wire Rope	290	7
	HYL-12	6320	1800	12	1140	—	Stainless Steel Wire Rope	360	9.2