

W22FD Marine Industrial Washing Machine

1.The shell adopts stainless steel, durable; 2.The automatic automatic watering, pre washing, rinsing, bleaching, clear ...



Category	Electric Heater
----------	-----------------

Standard	EN
Material	SS304
Weight / Size	Model Dimension(mm) Capacity(kg) Power (kw) Volts(v) HZ N/W(kg) W22FD 8...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Electric Heater	Model / SKU	W22FD-Marine-Industrial-Washing-Machine
Standard	EN	Material	SS304
Weight / Size	Model Dimension(mm) Capacity(kg) Power (kw) Volts(v) HZ N/W(kg) W22FD 850X740X1360 10 7 380V/415V/440V/480V-3P 50/60Hz 185 W25FD 850X740X1360 12 9 380V/415V/440V/480V-3P 50/60Hz 195 W35FD 850X820X1360 15 13 380V/415V/440V/480V-3P 50/60Hz 250 W45FD 850X920X1360 20 19 380V/415V/440V/480V-3P 50/60Hz 280	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	Product introduction: Technical data:
----------	---

Product introduction:

- 1.The shell adopts stainless steel, durable;
- 2.The automatic automatic watering, pre washing, rinsing, bleaching, clear the main program, storage of 30 kinds of washing procedures are available;
- 3.The unique suspension structure, low vibration without foundation, greatly improves the stability of the machine;
- 4.The imported frequency conversion system, ensure the minimum speed and the highest speed, the separation factor is greatly improved, which can ensure the washing quality, but also improves the dehydration rate;
- 5.The imported bearings and seal, ensure the operation accuracy and the reliability of the seal, reducing the failure rate;
- 6.A large stainless steel door, door control device West crystallization technology, greatly improves the safety of use;
- 7.It can remove the installation foot.

Technical data:

Model	Dimension(mm)	Capacity(kg)	Power (kw)	Volts(v)	HZ	N/W(kg)
W22FD	850X740X1360	10	7	380V/415V/440V/480V-3P	50/60Hz	185

W25FD	850X740X1360	12	9	380V/415V/440V/480V-3P	50/60Hz	195
W35FD	850X820X1360	15	13	380V/415V/440V/480V-3P	50/60Hz	250
W45FD	850X920X1360	20	19	380V/415V/440V/480V-3P	50/60Hz	280