

SENSOR

WFS-2 Wind speed sensor

Power supply: DC 12-36V Measurement range:0.1 ~40 m/s Accuracy : < 30m/s±(0.5+0.05v) ≥ 30m/s±5% Starting speed: < 0.1m/s Response time : < 0.5s Working Temperature - 20°C~ + 70°C Humidity : 20% - 90% RH(25...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Sensor
Standard	EN
Material	20% - 90% RH(25°C No condensation) Material:ABS + PC Output signal type:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sensor	Model / SKU	WFS-2-Wind-speed-sensor
Standard	EN	Material	20% - 90% RH(25°C No condensation) Material:ABS + PC Output signal type:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China WFS-2 Wind speed sensor:

Power supply: DC 12-36V
Measurement range:0.1 ~40 m/s
Accuracy : < 30m/s±(0.5+0.05v) ≥ 30m/s±5%
Starting speed: < 0.1m/s
Response time : < 0.5s
Working Temperature - 20°C~ + 70°C
Humidity : 20% - 90% RH(25°C No condensation)
Material:ABS + PC

Output signal type:
WFS-2-2 : 4~20 mA
WFS-2-3 : 0 ~ 5 V
WFS-2-4 : RS 485

