

SEWAGE PUMP

WQ (D) cutting submersible pump

WQ (D) cutting submersible pump Application Severely polluted waste water of factories, residence, hospitals, hotels, municipal works, marsh gas tanks in countryside, dredging of river and sea. ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Sewage Pump
Standard	EN
Material	Stainless steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sewage Pump	Model / SKU	WQ-D-cutting-submersible-pump
Standard	EN	Material	Stainless steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- WQ (D) cutting submersible pump
 - Features
- Application
 - Technical parameter

WQ (D) cutting submersible pump

Application

Severely polluted waste water of factories, residence, hospitals, hotels, municipal works, marsh gas tanks in countryside, dredging of river and sea.

Features

With casing of stainless steel precision casting, it is corrosion-resistant, environment-friendly, durable, high in head and large in flow rate. It uses motor of F insulation grade. On the base of this style, the pump can be installed with automatic agitator device, which rotates with shaft of motor, produces very strong agitation force, inhale sediments in the sump after mixes blend to become session to the pump then eject it. Pump more than 11kw could be with double-protection function.

Technical parameter

Model	Capacity (m3/h)	Head (m)	Power (KW)	Voltage (V)	Outlet Diameter(mm)
50WQ10-10-0.75S	10	10	0.75	220/380	50
50WQ15-10-1.1S	15	10	1.1	220/380	50
50WQ-15-12-1.5S	15	12	1.5	220/380	50
50WQ15-20-2.2S	15	20	2.2	380	50
65WQ25-15-2.2S	25	15	2.2	380	65
80WQ40-9-2.2S	40	9	2.2	380	80
100WQ50-7-2.2S	50	7	2.2	380	100
50WQ15-25-3S	15	25	3	380	50
80WQ40-15-3S	40	15	3	380	80
100WQ50-10-3S	50	10	3	380	100
50WQ15-32-4S	15	32	4	380	50
65WQ25-25-4S	25	25	4	380	65
80WQ40-18-4S	40	18	4	380	80
100WQ50-15-4S	50	15	4	380	100
50WQ20-32-5.5S	20	32	5.5	380	50
65WQ30-25-5.5S	30	25	5.5	380	65
80WQ50-18-5.5S	50	18	5.5	380	80
100WQ80-10-5.5S	80	10	5.5	380	100

150WQ100-7.5-5.5S	100	7.5	5.5	380	150
50WQ20-40-7.5S	20	40	7.5	380	50
65WQ30-32-7.5S	30	32	7.5	380	65
80WQ45-22-7.5S	45	22	7.5	380	80
100WQ80-15-7.5S	80	15	7.5	380	100
150WQ100-10-7.5S	100	10	7.5	380	150
150WQ-140-7-7.5S	140	7	7.5	380	150
50WQ25-50-11S	25	50	11	380	50
80WQ50-32-11S	50	32	11	380	80
100WQ100-20-11S	100	20	11	380	100
150WQ150-12-11S	150	12	11	380	150
200WQ200-10-11S	200	10	11	380	200
50WQ25-55-15S	25	55	15	380	50
80WQ70-30-15S	70	30	15	380	80
100WQ100-25-15S	100	25	15	380	100
150WQ150-15-15S	150	15	15	380	150
200WQ200-12-15S	200	12	15	380	200
50WQ25-60-18.5S	25	60	18.5	380	50
80WQ70-35-18.5S	70	35	18.5	380	80
100WQ100-30-18.5S	100	30	18.5	380	100
150WQ150-20-18.5S	150	20	18.5	380	150
200WQ200-15-18.5S	200	15	18.5	380	200
50WQ25-65-22S	25	65	22	380	50
80WQ70-40-22S	70	40	22	380	80

100WQ100-35-22S	100	35	22	380	100
150WQ150-25-22S	150	25	22	380	150
200WQ200-22-22S	200	22	22	380	200
300WQ400-10-22S	400	10	22	380	300