

HOT OIL TRANSFER PUMP

WRY Diesel Engine Driven Hot Oil Pump

WRY Diesel Engine Driven Hot Oil Pump General description WRY series hot oil has been widely used in the heating system in China.It is widely used in Oil, Rubber, Resin, Textile, Printing, Construction,Road c...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Hot Oil Transfer Pump
Standard	EN
Material	Carbon Steel, Alloy steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hot Oil Transfer Pump	Model / SKU	WRY-Diesel-Engine-Driven-Hot-Oil-Pump
Standard	EN	Material	Carbon Steel, Alloy steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China WRY Diesel Engine Driven Hot Oil Pump:



WRY Diesel Engine Driven Hot Oil Pump

General description

WRY series hot oil has been widely used in the heating system in China. It is widely used in Oil, Rubber, Resin, Textile, Printing, Construction, Road construction, Machinery and other industrial fields. Mainly used for transferring weak corrosion High temperature without solid particles. The transport medium's temperature should not exceed 350°C. It is driven by diesel engine.

Technical Parameter

Model	Capacity	Head	Speed	Power		Efficiency	NPSH
WRY	m ³ /h	m	rpm	Sh aft	Motor	%	m
65-50-180	32	32	2900	4.5	5.5	52	2.7
80-50-180	40	40	2900	6.7	7.5	63	3.1
100-65-190	60	38	2930	9.2	11	68	3.9
100-65-200	80	40	2930	12.5	15	70	3.5
100-65-230	100	55	2940	19.5	22	70	3.6
100-65-240	100	70	2950	25.5	30	69.8	4.1
100-65-257	100	80	2950	32.5	37	67	3.6