

HOT OIL TRANSFER PUMP

WRY Series Hot Oil Pump

WRY Series Hot Oil Pump General description WRY series hot oil has been widely used in the heating system in China.It is widely used in Oil, Rubber, Resin, Textile, Printing, Construction,Road construction,...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Hot Oil Transfer Pump
Standard	EN
Material	Carbon Steel, Alloy steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hot Oil Transfer Pump	Model / SKU	WRY-Series-Hot-Oil-Pump
Standard	EN	Material	Carbon Steel, Alloy steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- WRY Series Hot Oil Pump
 - Model explanation
- General description
 - Technical parameter

WRY Series Hot Oil Pump

General description

WRY series hot oil has been widely used in the heating system in China.It is widely used in Oil, Rubber, Resin, Textile, Printing, Construction,Road construction, Machinery and other industrial fields.Mainly used for transferring weak corrosion High temperature withoutsolid particles.The transport medium's temperature should not exceed 350C.

Model explanation

WRY 100-65-200

WRY: Air cooling hot oil pump

100: Inlet diameter mm

65: Outlet diameter mm

200: Impeller nominal diameter

Technical parameter

Model	Capacity	Head	Speed	Power		Efficiency	NPSH
WRY	m3/h	m	rpm	Sh aft	Mot or	%	m
26-20-100	4.5	15	2825	0.4 5	0.7 5	40	0.8
50-32-150	8	22	2840	1.1	1.5	42	1.6
50-32-160	10	25	2840	1.6	2.2	42	1.8
65-40-160	12.5	25	2880	1.9	3	45	2.2
50-50-170	12.5	32	2890	2.4	4	45	2.5
80-50-180	32	32	2900	5.3	5.5	52	2.7
80-50-170	40	25	2900	5.2	5.5	52	2.7
80-50-190	40	40	2900	6.9	7.5	63	3.1
80-50-170	60	20	2900	6.7	7.5	62	3.1
100-65-190	60	38	2930	9.8	11	63	3.9
100-65-200	80	40	2930	13. 6	15	64	3.5
100-65-220	58	50	2930	11. 9	15	66	3.5
100-65-230	100	55	2940	21. 4	22	67.5	3.6
125-100-190	155	30	2940	20	22	72	3.6
100-65-240	100	70	2950	28. 3	30	68	4.1
100-65-257	100	80	2950	32. 5	37	67	3.6
125-100-220	160	45	2950	25. 5	37	75	3.6
125-80-245	160	60	2970	35. 5	45	74	5

125-100-245	200	60	2970	42. 8	55	76	6
125-100-257	260	70	2970	64. 3	75	77	6.8
125-100-260	300	70	2970	75. 3	90	78	8
125-100-270	220	85	2970	68	90	76	6
150-100-270	340	76	2970	89. 5	110	78.6	8.5
150-125-270	400	78	2970	10 6.2	132	80	9.8