

WS-SHL Three Pulley Weight Sensor

Range: start from 500kg. Applicaton:Load sensing,transfer transportation system,wire rope pull strength measurement. Accuracy of measurement:
1.0±0.005mv/v Ultimate o...



We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Sensor	Model / SKU	WS-SHL-Three-Pulley-Weight-Sensor
Standard	EN	Material	1.0±0.005mv/v Ultimate overload:250%F.S Protection Class:IP68 Safe Overload:150%F.S Temperature range:-30 to 70 centigrade Features: Built-in film sensing element. Stainless steel material. The integrated amplifier circuit. Long term stability. Strong impact resistance. Suitable for dynamic and static measurements.
Weight / Size	start from 500kg. Applicaton:Load sensing,transfer transportation system,wire rope pull strength measurement. Accuracy of measurement:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China WS-SHL Three Pulley Weight Sensor:	■ Features:
----------	--	-------------

China WS-SHL Three Pulley Weight Sensor:

Range: start from 500kg.

Applicaton:Load sensing,transfer transportation system,wire rope pull strength measurement.

Accuracy of measurement: 1.0±0.005mv/v

Ultimate overload:250%F.S

Protection Class:IP68

Safe Overload:150%F.S

Temperature range:-30 to 70 centigrade

Features:

- Built-in film sensing element.
- Stainless steel material.
- The integrated amplifier circuit.
- Long term stability.

Strong impact resistance.

Suitable for dynamic and static measurements.

Tiny temperature drift error.