

YACHT WINDLASS & WINCH

Yatch windlass horizontal type

Yatch windlass horizontal type Features 1.Designed for automatic horizontal handling of chain only anchor rodes while offering an independent capstan for the retrieval of a secondary rope and chain rode or to...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Yacht Windlass & Winch
Standard	EN
Material	Stainless steel 304,316, 316L
Weight / Size	Specifications Model Weight Power Motor No load Max Max.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Yacht Windlass & Winch	Model / SKU	Yatch-windlass-horizontal-type
Standard	EN	Material	Stainless steel 304,316, 316L
Weight / Size	Specifications Model Weight Power Motor No load Max Max.	Surface	7.Marine-grade alloy casting pretreated, powder coated and finished with a two component white polyurethane paint.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Yatch windlass horizontal type
- Specifications
- Features

Yatch windlass horizontal type

Features

- 1.Designed for automatic horizontal handling of chain only anchor rodes while offering an independent capstan for the retrieval of a secondary rope and chain rode or toassit with docking procedures.
- 2.Fully automatic single dual direction chain-wheel operation.
- 3.Optional dual anchor handling with smooth independent control of each chain-wheel via cone clutches.
- 4. Simple deck mounted installation with no under deck parts.
- 5.Simplified maintenance with ability to strip the running gear (chain-wheel and drum) from the windlass without disturbing the windlass mounting.
- 6.Heavy duty, dual direction motor, designed for marine winches.
- 7.Marine-grade alloy casting pretreated, powder coated and finished with a two component white polyurethane paint.
- 8.Fit include hand-switch, control box and wrench.

Specifications

Model	Weight	Power	Motor	No load	Max	Max.	Line	Rope	Chain
	net(kg)		(W)	absorption	Load	Pull	Speed	Size	Size
YDH-011	16	12V/24V	600	50A	190kg	600kg	30m/min	12-14mm	6-7mm
YDH-012	25.2	12V/24V	1000	90A	350kg	750kg	25m/min	14-16mm	8-10mm
YDH-013	32	12V/24V	1400	125A	520kg	1100kg	25m/min	18-20mm	8-10mm
YDH-013	33.7	12V/24V	1600	140A	660kg	1400kg	20m/min	20-24mm	10-12mm
YDH-014	36	220V/380V	2000	6A	900kg	2000kg	20m/min	20-24mm	10-12.5mm
YDH-014	38	220V/380V	3000	9A	1200kg	2500kg	20m/min	20-24mm	10-12.5mm