

MARINE OIL WATER SEPERATOR

YSZ-1.0 15ppm Bilge Oily Water Separator

ISO9001 Supplier

Class Certificate

Export Supply

Description: YSZ-1.0 15ppm Bilge water separator is very suitable a small ship and Ocean Drilling Platform. It meet IMO MEPC.107(49), we export to South Korea, Singapore, Myanmar, Vietnam, Thailand, Malaysi...



Key Highlights

Category	Marine Oil Water Seperator
Standard	EN
Weight / Size	Model Number YSZ-1 Treatment capability (m3 per hour) 1 Discharging stan...
Certificate	CCS, BV, DNV-GL, BV, ABS, NK

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Oil Water Seperator	Model / SKU	YSZ-1-0-15ppm-Bilge-Oily-Water-Separator
Standard	EN	Weight / Size	Model Number YSZ-1 Treatment capability (m3 per hour) 1 Discharging standard Equal or less than 15ppm,satisfy with IMO MEPC.107 (49) Working pressure Equal or less than 0.3 Mpa Plunger pump Model DZ-1000 Discharing pressure(Mpa) 0.3 Suction lift(m) 6 Motor power(kw) 0.37 Electric heating power 2 Power supply 3 Phase 380V 50HZ, 3 Phase 440V 60HZ Control mode Automatic Oil drainage mode Automatic or manual Weight(kg) 600 Size(mm) 1470x820x1700
Certificate	CCS, BV, DNV-GL, BV, ABS, NK	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	Description: Technical Data:
----------	--

Description:

YSZ-1.0 15ppm Bilge water separator is very suitable a small ship and Ocean Drilling Platform.

It meet IMO MEPC.107(49), we export to South Korea, Singapore, Myanmar, Vietnam, Thailand, Malaysia, Indonesia, the most competitive market at the best price, serving the vast number of shipyards and dealers.

Technical Data:

Model Number		YSZ-1
Treatment capability (m3 per hour)		1
Discharging standard		Equal or less than 15ppm,satisfy with IMO MEPC.107 (49)
Working pressure		Equal or less than 0.3 Mpa
Plunger pump	Model	DZ-1000
	Discharing pressure(Mpa)	0.3
	Suction lift(m)	6
	Motor power(kw)	0.37

Electric heating power	2
Power supply	3 Phase 380V 50HZ, 3 Phase 440V 60HZ
Control mode	Automatic
Oil drainage mode	Automatic or manual
Weight(kg)	600
Size(mm)	1470x820x1700