

OIL PURIFIER

ZYZ Series OLTC On Live Oil Purifier

China ZYZ Series OLTC On Live Oil Purifier: ZYZ on load switch oil filter This transformer OLTC oil filter as a bypass oil circulation filtration equipment, insulating oil can be decomposed and filtrat...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Oil Purifier
Standard	DIN
Material	All-weather box, stainless steel material, wall mounted and fixed instal...
Weight / Size	Rated pump pressure 0.5Mpa Alarm pressure 0.4Mpa Motor power 200W Rated ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Oil Purifier	Model / SKU	ZYZ-Series-OLTC-On-Live-Oil-Purifier
Standard	DIN	Material	All-weather box, stainless steel material, wall mounted and fixed installation.
Weight / Size	Rated pump pressure 0.5Mpa Alarm pressure 0.4Mpa Motor power 200W Rated flow 10L/min Filter impurity filter precision ≤1μm Cleanliness 5 ~ 6 Stage (NAS 1638 Standard) Water content after filtration ≤25ppm Leakage current ≤0.75mA Medium temperature -30 ~ 100°C Box wall thickness 2mm Power 380V/50Hz Box protection class IP54 Weight 45kg Exterior dimension 550×750×300	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China ZYZ Series OLTC On Live Oil Purifier:	■ China ZYZ Series OLTC On Live Oil Purifier:
	■ Technical features:	

China ZYZ Series OLTC On Live Oil Purifier:

China ZYZ Series OLTC On Live Oil Purifier:

ZYZ on load switch oil filter

This transformer OLTC oil filter as a bypass oil circulation filtration equipment, insulating oil can be decomposed and filtration pollution under the state of no power cut, the removal of oil in water, free carbon and oxides, improve the dielectric strength of insulating oil, ensure the quality of oil. To extend the operation life of on load tap changer, to reduce the number of times of stopping oil change, to reduce the operation and maintenance cost, to improve the reliability and economy of power transformer, and to maintain the simplicity of maintenance.

Technical features:

1. All-weather box, stainless steel material, wall mounted and fixed installation.
2. Temperature and humidity relay, automatic adjustment of temperature and humidity equipment.
3. According to the actual situation to choose the mode of operation, can be automatically controlled, daily start can also be manually operated;
4. Oil pump with motor and pump body integration, compact structure, and low noise;

5. The has the function of remote monitoring of the operation and fault signal, the remote timing start, and the synchronous start of the on load tap changer;

6. Using high quality filter, quality assurance. Long life design, stable and reliable operation.

Rated pump pressure	0.5Mpa	Alarm pressure	0.4Mpa
Motor power	200W	Rated flow	10L/min
Filter impurity filter precision	≤1μm	Cleanliness	5 ~ 6 Stage (NAS 1638 Standard)
Water content after filtration	≤25ppm	Leakage current	≤0.75mA
Medium temperature	-30 ~ 100°C	Box wall thickness	2mm
Power	380V/50Hz	Box protection class	IP54
Weight	45kg	Exterior dimension	550×750×300